



5411 Seymour Hwy Wichita Falls, TX 76301

Tel: 940-767-7694 Fax: 940-687-0751

WWW.NITROUSEXPRESS.COM

Caution – EXTREME DANGER – Caution

Do not use or mix any other manufacturer's products with any Nitrous Express products.

Do not use or mix any Nitrous Express products with any other manufacturer's products.

THESE INSTRUCTIONS APPLY TO NITROUS EXPRESS PRODUCTS ONLY!

FOR SANCTIONED RACE USE ONLY - NOT FOR SALE OR USE IN CALIFORNIA

Fuel Rail Adapter Installation Instructions

1. Remove the vehicle's factory fuel line from the fuel rail connection using a fuel line disconnect tool as illustrated below.

WARNING: THE FUEL RAIL AND/OR FUEL LINES ARE UNDER HIGH PRESSURE. USE EXTREME CAUTION WHEN DISCONNECTING ANY FUEL LINE. QUICKLY COLLECT AND PROPERLY DISPOSE OF ANY EXCESS FUEL SPILLAGE.



2. Clean and inspect the vehicles factory fuel rail and line for any damage, such as burrs, nicks, or other features that can be detrimental for a proper seal. Repair or replace any damaged components before continuing with the install.
3. Lightly lubricate the male connections where the o-rings of the NX fuel line adapter will make contact with the factory fuel line.
4. Install the NX fuel line adapter between the factory fuel line and the factory fuel rail.
5. Ensure that the NX fuel line adapter clip and the factory fuel line connections are properly engaging by pulling on the connections and inspecting the clips.
6. The Fuel Rail Adapter has two 1/8"NPT holes. Using NX thread sealer, install the 1/8"NPT x 4AN Fitting in one, and the 1/8NPT hex plug in the other. **NOTE: NX Thread Sealer must be used on the pipe threads. DO NOT USE ON FLARE SIDE of fitting.**
7. Pressure test the connection, inspecting for leaks prior to starting the engine



**WARNING: Cancer and
Reproductive Harm-**
www.P65Warnings.ca.gov