



P/N S197-1020 Made in USA

2005-14 Hood Bumper Bezel Installation Instructions

Thank you for your purchase of SilverHorse Racing products. Please read all directions before beginning the installation. A factory shop manual should be available for reference during installation. If, after reading these and any accompanying directions, you feel that you may not be able to complete the installation safely and properly, please seek out professional installation by certified technicians. Please read and understand our product purchase agreement (included on yellow sheet) prior to starting installation. Vehicle should be off with key removed from ignition and in park with parking brake set prior to beginning installation.

1. Clean top of radiator support area and existing rubber hood bumpers.
2. Take note the orientation of the arrow on the top of the rubber hood bumper, as well as how many threads are exposed in case you need to remove the bumpers.
3. With the larger end pointing down toward the radiator, carefully slide the bezel over the hood bumper and into place. The hexagon shape on the top of the hood bumper should retain the bezel on its smaller interior lip just under the hex.
4. If the bezel is loose due to the varying sizes of hood bumpers (they can be different diameters even on the same vehicle), the use of black silicone is recommended to retain the bezel to the hood bumper. If this is required, it is recommended that just the minimum required is used on the sides of the hood bumper itself, then place the bezel in position and allow to dry. Black automotive gasket silicone is not included, but is available at most any automotive or hardware store.

If you have any questions, feel free to contact us at the number listed below or via email.

Tech Questions: (321)-722-2813.

Email us -

Tech@SilverHorseRacing.com

“If it’s not good enough for our cars, we won’t make it for yours.”

