

Race Star Wheel Applications

These are recommended fitments for O.E. vehicles.

BUICK CARS ALL YEARS

73-77 Regal, GS 5x4.75 70.3 0-15 7/16 (A-Body)

oe fr	14	6.00		0.00		3.50	3.50					
oe rr	14	6.00		0.00		3.50	3.50					
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe	32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	0.00		XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	0.12			XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	1.00			XX	
rr	15	8.00	-580248	0.00		4.50	4.50	1.00		XX	XX	
rr	15	10.00	-510250	0.00		5.50	5.50	2.00		XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	0.25		XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	0.25			XX	XX
rr	17	8.00	-780248	0.00		4.50	4.50	1.00			XX	
rr	17	9.50	-795249	0.00		5.25	5.25	1.75			XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	0.50				XX
fr/rr	18	7.00	-870247	0.00		4.00	4.00	0.50	XX			
rr	18	10.00	-810250	0.00		5.50	5.50	2.00	XX			
fr/rr	20	8.50	-085248	0.00		4.75	4.75	1.25	XX			
rr	20	10.00	-010250	0.00		5.50	5.50	2.00	XX			
	601-1414-10		7/16 closed lug kit, 10 pk (92 series)								XX	XX
	601-1414-20		7/16 closed lug kit, 20 pk (92 series)								XX	XX
	601-1424-10		7/16 open lug kit, 10 pk (92 series)								XX	XX
	601-1424-20		7/16 open lug kit, 20 pk (92 series)								XX	XX
	602-2437-10		7/16 closed lug kit, 10 pk (32, 95)									XX
	602-2437-20		7/16 closed lug kit, 20 pk (32, 95)									XX

78-81 Regal, T-Type, Grand National, GSX 5x4.75 70.3 0-15 7/16

oe fr	15	6.00		15.00		4.09	2.91					
oe rr	15	6.00		15.00		4.09	2.91					
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe	32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	0.60		XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	0.71			XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	1.59			XX	
rr	15	8.00	-580248	0.00		4.50	4.50	1.59		XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	0.84		XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	0.84			XX	XX
fr/rr	17	8.00	-780248	0.00		4.50	4.50	1.59			XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	1.09			XX	XX
fr/rr	18	7.00	-870247	0.00		4.00	4.00	1.09	XX			
rr	18	8.50	-885250	17.50		5.44	4.06	1.15			XX	XX
fr/rr	20	8.50	-085248	0.00		4.75	4.75	1.84	XX			
	601-1414-10		7/16 closed lug kit, 10 pk (92 series)								XX	XX

	601-1414-20		7/16 closed lug kit, 20 pk (92 series)							XX	XX		
	601-1424-10		7/16 open lug kit, 10 pk (92 series)							XX	XX		
	601-1424-20		7/16 open lug kit, 20 pk (92 series)							XX	XX		
	602-2437-10		7/16 closed lug kit, 10 pk (32, 95)									XX	
	602-2437-20		7/16 closed lug kit, 20 pk (32, 95)									XX	
82-87 Regal, T-Type, Grand National, GSX 5x4.75 70.3 0-15 12mm													
oe fr	15	6.00		15.00		4.09	2.91						
oe rr	15	6.00		15.00		4.09	2.91						
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	0.60			XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	0.71				XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	1.59				XX	
rr	15	8.00	-580248	0.00		4.50	4.50	1.59			XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	0.84			XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	0.84				XX	XX
fr/rr	17	8.00	-780248	0.00		4.50	4.50	1.59				XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	1.09				XX	XX
fr/rr	18	7.00	-870247	0.00		4.00	4.00	1.09		XX			
rr	18	8.50	-885250	17.50		5.44	4.06	1.15				XX	XX
fr/rr	20	8.50	-085248	0.00		4.75	4.75	1.84		XX			
	601-1412-10		12x1.5 closed lug kit, 10 pk (92 series)								XX	XX	
	601-1412-20		12x1.5 closed lug kit, 20 pk (92 series)								XX	XX	
	601-1422-10		12x1.5 open lug kit, 10 pk (92 series)								XX	XX	
	601-1422-20		12x1.5 open lug kit, 20 pk (92 series)								XX	XX	
	602-2439-10		12x1.5 closed lug kit, 10 pk (92 series)							XX			XX
	602-2439-20		12x1.5 closed lug kit, 20 pk (92 series)							XX			XX
64-67 Skylark, GS 5x4.75 70.3 0-15 7/16													
oe fr	14	6.00		15.00		4.09	2.91						
oe rr	14	6.00		15.00		4.09	2.91						
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	0.60			XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	0.71				XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	1.59				XX	
rr	15	8.00	-580248	0.00		4.50	4.50	1.59			XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	0.84			XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	0.84				XX	XX
fr/rr	17	8.00	-780248	0.00		4.50	4.50	1.59				XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	1.09				XX	XX
fr/rr	18	7.00	-870247	0.00		4.00	4.00	1.09		XX			
rr	18	8.50	-885250	17.50		5.44	4.06	1.15				XX	XX
fr/rr	20	8.50	-085248	0.00		4.75	4.75	1.84		XX			
	601-1414-10		7/16 closed lug kit, 10 pk (92 series)								XX	XX	

	601-1414-20		7/16 closed lug kit, 20 pk (92 series)							XX	XX		
	601-1424-10		7/16 open lug kit, 10 pk (92 series)							XX	XX		
	601-1424-20		7/16 open lug kit, 20 pk (92 series)							XX	XX		
	602-2437-10		7/16 closed lug kit, 10 pk (32, 95)							XX		XX	
	602-2437-20		7/16 closed lug kit, 20 pk (32, 95)							XX		XX	
68-72 Skylark, GS, GSX 5x4.75 70.3 0-15 7/16 (A-Body)													
oe fr	14	6.00		0.00		3.50	3.50						
oe rr	14	6.00		0.00		3.50	3.50						
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	0.00			XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	0.12				XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	1.00				XX	
rr	15	8.00	-580248	0.00		4.50	4.50	1.00			XX	XX	
rr	15	10.00	-510250	0.00		5.50	5.50	2.00			XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	0.25			XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	0.25				XX	XX
rr	17	8.00	-780248	0.00		4.50	4.50	1.00				XX	
rr	17	9.50	-795249	0.00		5.25	5.25	1.75					
fr	18	5.00	-850245	-25.40		2.00	4.00	0.50				XX	
fr/rr	18	7.00	-870247	0.00		4.00	4.00	0.50		XX			
rr	18	10.00	-810250	0.00		5.50	5.50	2.00		XX			
fr/rr	20	8.50	-085248	0.00		4.75	4.75	1.25		XX			
rr	20	10.00	-010250	0.00		5.50	5.50	2.00		XX			
	601-1414-10		7/16 closed lug kit, 10 pk (92 series)								XX	XX	
	601-1414-20		7/16 closed lug kit, 20 pk (92 series)								XX	XX	
	601-1424-10		7/16 open lug kit, 10 pk (92 series)								XX	XX	
	601-1424-20		7/16 open lug kit, 20 pk (92 series)								XX	XX	
	602-2437-10		7/16 closed lug kit, 10 pk (32, 95)							XX			XX
	602-2437-20		7/16 closed lug kit, 20 pk (32, 95)							XX			XX

Race Star Wheel Applications

These are recommended fitments for O.E. vehicles.

CHEVROLET CAMARO/ PONTIAC FIREBIRD ALL YEARS

67-68 CAMARO/ FIREBIRD 5x4.75 70.3 0-15 7/16

oe fr	14	6.00		0.00		3.50	3.50							
oe rr	14	6.00		0.00		3.50	3.50							
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bsp space in</i>	<i>fsp space in</i>	<i>stick out/ oe</i>		<i>F1</i>	<i>32</i>	<i>82</i>	<i>92</i>	<i>95</i>
fr	15	3.75	-537240	-28.70		1.25	3.50	0.00				XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	0.12					XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	1.00					XX	
rr	15	8.00	-580247	-12.70		4.00	5.00	1.50					XX	
rr	15	8.00	-580248	0.00		4.50	4.50	1.00				XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	0.25				XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	0.25					XX	XX
rr	17	8.00	-780248	0.00		4.50	4.50	1.00					XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	0.50					XX	
fr	18	7.00	-870247	0.00		4.00	4.00	0.50			XX			
rr	20	8.50	-085248	0.00		4.75	4.75	1.25			XX			
	601-1414-10		7/16 closed lug kit, 10 pk (82, 92 series)									XX	XX	
	601-1414-20		7/16 closed lug kit, 20 pk (82, 92 series)									XX	XX	
	601-1424-10		7/16 open lug kit, 10 pk (82, 92 series)									XX	XX	
	601-1424-20		7/16 open lug kit, 20 pk (82, 92 series)									XX	XX	
	602-2437-10		7/16 closed lug kit, 10 pk (32, 95 series)								XX			XX
	602-2437-20		7/16 closed lug kit, 20 pk (32, 95 series)								XX			XX

69 CAMARO/ FIREBIRD 5x4.75 70.3 0-15 7/16

oe fr	14	6.00		0.00		3.50	3.50							
oe rr	14	6.00		0.00		3.50	3.50							
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bsp space in</i>	<i>fsp space in</i>	<i>stick out/ oe</i>		<i>F1</i>	<i>32</i>	<i>82</i>	<i>92</i>	<i>95</i>
fr	15	3.75	-537240	-28.70		1.25	3.50	0.00				XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	0.12					XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	1.00					XX	
rr	15	8.00	-580247	-12.70		4.00	5.00	1.50					XX	
rr	15	8.00	-580248	0.00		4.50	4.50	1.00				XX	XX	
rr	15	10.00	-510250	0.00		5.50	5.50	2.00				XX	XX	

fr	17	4.50	-745242	-25.40		1.75	3.75	0.25				XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	0.25					XX	XX
rr	17	8.00	-780248	0.00		4.50	4.50	1.00					XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	0.50					XX	
fr	18	7.00	-870247	0.00		4.00	4.00	0.50			XX			
rr	18	10.00	-810250	0.00		5.50	5.50	2.00			XX			
fr	20	8.50	-085248	0.00		4.75	4.75	1.25			XX			
rr	20	10.00	-000250	0.00		5.50	5.50	2.00			XX			
	601-1414-10		7/16 closed lug kit, 10 pk (82, 92 series)									XX	XX	
	601-1414-20		7/16 closed lug kit, 20 pk (82, 92 series)									XX	XX	
	601-1424-10		7/16 open lug kit, 10 pk (82, 92 series)									XX	XX	
	601-1424-20		7/16 open lug kit, 20 pk (82, 92 series)									XX	XX	
	602-2437-10		7/16 closed lug kit, 10 pk (32, 95 series)								XX			XX
	602-2437-20		7/16 closed lug kit, 20 pk (32, 95 series)								XX			XX
70-81 (2nd GEN) CAMARO/ FIREBIRD 5x4.75 70.3 0-15 7/16														
oe fr	15	7.00		0.00		4.00	4.00							
oe rr	15	7.00		0.00		4.00	4.00							
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		<i>F1</i>	<i>32</i>	<i>82</i>	<i>92</i>	<i>95</i>
fr	15	3.75	-537240	-28.70		1.25	3.50	-0.50				XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	-0.38					XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	0.50					XX	
fr	15	8.00	-580247	-12.70		4.00	5.00	1.00					XX	
rr	15	8.00	-580247	-12.70		4.00	5.00	1.00					XX	
fr	15	8.00	-580248	0.00		4.50	4.50	0.50				XX	XX	
rr	15	8.00	-580248	0.00		4.50	4.50	0.50				XX	XX	
rr	15	10.00	-510250	0.00		5.50	5.50	1.50					XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	-0.25		XX		XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	-0.25					XX	XX
fr	17	8.00	-780248	0.00		4.50	4.50	0.50					XX	
rr	17	8.00	-780248	0.00		4.50	4.50	0.50					XX	
rr	17	9.50	-795249	0.00		5.25	5.25	1.25					XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	0.00					XX	
fr	18	7.00	-870247	0.00		4.00	4.00	0.00			XX			
fr	18	8.50	-885250	17.50		5.44	4.06	0.06					XX	
rr	18	10.00	-810250	0.00		5.50	5.50	1.50			XX			
fr	20	8.50	-085248	0.00		4.75	4.75	0.75			XX			
rr	20	10.00	-000250	0.00		5.50	5.50	1.50			XX			

	601-1414-10		7/16 closed lug kit, 10 pk (82, 92 series)									XX	XX	
	601-1414-20		7/16 closed lug kit, 20 pk (82, 92 series)									XX	XX	
	601-1424-10		7/16 open lug kit, 10 pk (82, 92 series)									XX	XX	
	601-1424-20		7/16 open lug kit, 20 pk (82, 92 series)									XX	XX	
	602-2437-10		7/16 closed lug kit, 10 pk (32, 95 series)								XX			XX
	602-2437-20		7/16 closed lug kit, 20 pk (32, 95 series)								XX			XX
82-92 (3rd GEN) CAMARO/ FIREBIRD 5x4.75 70.3 0-15 12mm 26" OD tire														
oe fr	16	8.00		15.00		5.09	3.91							
oe rr	16	8.00		15.00		5.09	3.91							
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		F1	32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	-0.40				XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	-0.29					XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	0.59					XX	
fr	15	8.00	-580247	-12.70		4.00	5.00	1.09					XX	
rr	15	8.00	-580247	-12.70		4.00	5.00	1.09					XX	
fr	15	8.00	-580248	0.00		4.50	4.50	0.59				XX	XX	
rr	15	8.00	-580248	0.00		4.50	4.50	0.59				XX	XX	
rr	15	10.00	-510250	0.00		5.50	5.50	1.59				XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	-0.16				XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	-0.16					XX	XX
fr	17	8.00	-780248	0.00		4.50	4.50	0.59					XX	
rr	17	8.00	-780248	0.00		4.50	4.50	0.59					XX	
rr	17	9.50	-795249	0.00		5.25	5.25	1.34					XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	0.09					XX	XX
rr	18	7.00	-870247	0.00		4.00	4.00	0.09			XX			
fr	18	8.50	-885250	17.50		5.44	4.06	0.15					XX	XX
rr	18	10.00	-810250	0.00		5.50	5.50	1.59			XX			
fr	20	8.50	-085248	0.00		4.75	4.75	0.84			XX			
rr	20	10.00	-000250	0.00		5.50	5.50	1.59			XX			
	601-1412-10		12x1.5 closed lug kit, 10 pk (82, 92 series)									XX	XX	
	601-1412-20		12x1.5 closed lug kit, 20 pk (82, 92 series)									XX	XX	
	601-1422-10		12x1.5 open lug kit, 10 pk (82, 92 series)									XX	XX	
	601-1422-20		12x1.5 open lug kit, 20 pk (82, 92 series)									XX	XX	
	602-2439-10		12x1.5 closed lug kit, 10 pk (32, 95 series)											XX

	602-2439-20	12x1.5 closed lug kit, 20 pk (32, 95 series)													XX
93-02 (4th GEN) CAMARO/ FIREBIRD 5x4.75 70.3 35-45 12mm 26" OD tire															
oe fr	17	8.00		35.00		5.88	3.12								
oe rr	17	11.00		45.00		7.77	4.23								
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		F1	32	82	92	95	
r star fr	15	3.75	-537240	-28.70		1.25	3.50	0.38				XX	XX		
r star fr	15	5.00	-550244	-15.80		2.38	3.62	0.50					XX		
r star rr	15	8.00	-580250	19.00		5.25	3.75	-0.48				XX	XX		
r star rr	15	10.00	-510254	44.00		7.23	3.77	-0.46		XX		XX	XX	XX	
r star fr	17	4.50	-745242	-25.40		1.75	3.75	0.63				XX	XX	XX	
r star fr	17	4.50	-745245	-12.00		2.28	3.22	0.10		XX			XX	XX	
r star fr	17	7.00	-770247	6.40		4.25	3.75	0.63					XX	XX	
r star fr	17	7.00	-770249	22.00		4.87	3.13	0.01					XX	XX	
r star fr	17	8.00	-780250	25.40		5.50	3.50	0.38					XX		
r star rr	17	9.50	-795252	20.00	32.00	6.51	3.99	-0.24					XX		
r star rr	17	10.50	-705253	32.00	44.00	7.48	4.02	-0.21					XX	XX	
r star fr	18	5.00	-850246	-6.00		2.76	3.24	0.11					XX	XX	
r star fr	18	7.00	-870249	22.00		4.87	3.13	-1.09			XX				
r star rr	18	8.50	-885250	17.50		5.44	4.06	-0.17					XX	XX	
r star fr	18	8.50	-885251	36.00		6.17	3.33	0.21					XX		
r star rr	18	10.00	-810253	35.00		6.88	4.12	-0.11			XX				
r star rr	18	10.50	-805253	32.00	44.00	7.48	4.02	-0.21					XX	XX	
r star fr	20	8.50	-085251	35.00		6.13	3.37	-0.86			XX				
r star rr	20	10.00	-000253	35.00		6.88	4.12	-0.11			XX				
	601-1412-10	12x1.5 closed lug kit, 10 pk (82, 92 series)											XX	XX	
	601-1412-20	12x1.5 closed lug kit, 20 pk (82, 92 series)											XX	XX	
	601-1422-10	12x1.5 open lug kit, 10 pk (82, 92 series)											XX	XX	
	601-1422-20	12x1.5 open lug kit, 20 pk (82, 92 series)											XX	XX	
	602-2439-10	12x1.5 closed lug kit, 10 pk (F1, 32, 95 series)													XX
	602-2439-20	12x1.5 closed lug kit, 20 pk (F1, 32, 95 series)													XX
2010-15 (5th GEN) Camaro SS 5x120 70.3id 35-45os 14mmx1.5 28.7"OD tire															
oe fr	20	8.00		15.00		5.09	3.91								
	20	10.00		23.00		6.41	4.59								
oe rr	20	9.00		35.00		6.38	3.62								
	20	11.00		45.00		7.77	4.23								
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		F1	32	82	92	95	

fr	17	4.50	-745242	-25.00		1.77	3.73	-0.86		XX			XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	-0.16					XX	XX
rr	17	9.50	-795252	19.00		6.00	4.50	0.27					XX	
rr	17	10.50	-705253	32.00		7.01	4.49	0.26					XX	XX
fr	18	5.00	-850245	-25.40		2.00	4.00	0.09					XX	XX
fr	18	8.50	-885250	17.50		5.44	4.06	0.15					XX	XX
rr	18	10.50	-805253	32.00		7.01	4.49	0.26					XX	XX
fr	20	10.00	-010252	22.00		6.37	4.63	0.04						XX
rr	20	11.00	-011254	41.00		7.61	4.39	0.16						XX
		601-1428-10	14x1.5 closed lug kit, 10 pk (92 series)										XX	
		601-1428-20	14x1.5 closed lug kit, 20 pk (92 series)										XX	
		601-1430-10	14x1.5 open lug kit, 10 pk (92 series)										XX	
		601-1430-20	14x1.5 open lug kit, 20 pk (92 series)										XX	
		602-2428-10	14x1.5 closed lug kit, 10 pk (F1, 95 series)							XX				XX
		602-2428-20	14x1.5 closed lug kit, 20 pk (F1, 95 series)							XX				XX

Race Star Wheel Applications

These are recommended fitments for O.E. vehicles.

CHEVROLET CARS ALL YEARS

58-70 Biscayne, Bel Air, Impala, Caprice, Super Sport 5x4.75 70.3 0-15 7/16 (B-Body)

oe fr	14	7.00		15.00		4.59	3.41						
oe rr	14	7.00		15.00		4.59	3.41						
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	0.10			XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	0.21				XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	1.09				XX	
rr	15	8.00	-580248	0.00		4.50	4.50	1.09			XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	0.34			XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	0.34				XX	XX
fr/rr	17	8.00	-780248	0.00		4.50	4.50	1.09				XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	0.59				XX	XX
fr/rr	18	7.00	-870247	0.00		4.00	4.00	0.59		XX			
rr	18	8.50	-885250	17.50		5.44	4.06	0.65				XX	XX
fr/rr	20	8.50	-085248	0.00		4.75	4.75	1.34		XX			
*Denotes: Relocating rear shocks inboard may be required													
	601-1414-10		7/16 closed lug kit, 10 pk (92 series)									XX	XX
	601-1414-20		7/16 closed lug kit, 20 pk (92 series)									XX	XX
	601-1424-10		7/16 open lug kit, 10 pk (92 series)									XX	XX
	601-1424-20		7/16 open lug kit, 20 pk (92 series)									XX	XX
	602-2437-10		7/16 closed lug kit, 10 pk (32, 95)							XX			XX
	602-2437-20		7/16 closed lug kit, 20 pk (32, 95)							XX			XX

64-67 Chevelle, Malibu, 300, El Camino 5x4.75 70.3 0-15 7/16 (A-Body)

oe fr	14	6.00		15.00		4.09	2.91						
oe rr	14	6.00		15.00		4.09	2.91						
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	0.60			XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	0.71				XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	1.59				XX	

rr	15	8.00	-580248	0.00		4.50	4.50	1.59			XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	0.84			XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	0.84				XX	XX
fr/rr	17	8.00	-780248	0.00		4.50	4.50	1.59				XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	1.09				XX	XX
fr/rr	18	7.00	-870247	0.00		4.00	4.00	1.09		XX			
rr	18	8.50	-885250	17.50		5.44	4.06	1.15				XX	XX
fr/rr	20	8.50	-085248	0.00		4.75	4.75	1.84		XX			
	601-1414-10		7/16 closed lug kit, 10 pk (92 series)								XX	XX	
	601-1414-20		7/16 closed lug kit, 20 pk (92 series)								XX	XX	
	601-1424-10		7/16 open lug kit, 10 pk (92 series)								XX	XX	
	601-1424-20		7/16 open lug kit, 20 pk (92 series)								XX	XX	
	602-2437-10		7/16 closed lug kit, 10 pk (32, 95)							XX			XX
	602-2437-20		7/16 closed lug kit, 20 pk (32, 95)							XX			XX
68-72 Chevelle, Malibu, 300, Super Sport, El Camino 5x4.75 70.3 0-15 7/16 (A-Body)													
oe fr	14	6.00		0.00		3.50	3.50						
oe rr	14	6.00		0.00		3.50	3.50						
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	0.00			XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	0.12				XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	1.00				XX	
fr/rr	15	8.00	-580248	0.00		4.50	4.50	1.00			XX	XX	
rr	15	10.00	-510250	0.00		5.50	5.50	2.00			XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	0.25			XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	0.25				XX	XX
fr/rr	17	8.00	-780248	0.00		4.50	4.50	1.00				XX	
rr	17	9.50	-795249	0.00		5.25	5.25	1.75				XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	0.50				XX	
fr/rr	18	7.00	-870247	0.00		4.00	4.00	0.50		XX			
rr	18	10.00	-810250	0.00		5.50	5.50	2.00		XX			
fr/rr	20	8.50	-085248	0.00		4.75	4.75	1.25		XX			
rr	20	10.00	-010250	0.00		5.50	5.50	2.00		XX			

	601-1414-10		7/16 closed lug kit, 10 pk (92 series)							XX	XX		
	601-1414-20		7/16 closed lug kit, 20 pk (92 series)							XX	XX		
	601-1424-10		7/16 open lug kit, 10 pk (92 series)							XX	XX		
	601-1424-20		7/16 open lug kit, 20 pk (92 series)							XX	XX		
	602-2437-10		7/16 closed lug kit, 10 pk (32, 95)							XX		XX	
	602-2437-20		7/16 closed lug kit, 20 pk (32, 95)							XX		XX	
73-77 Chevelle, Malibu, Super Sport, El Camino, Monte Carlo 5x4.75 70.3 0-15 7/16 (A-Body)													
oe fr	15	7.00		0.00		4.00	4.00						
oe rr	15	7.00		0.00		4.00	4.00						
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	-0.50			XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	-0.38				XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	0.50				XX	
fr/rr	15	8.00	-580248	0.00		4.50	4.50	0.50			XX	XX	
rr	15	10.00	-510250	0.00		5.50	5.50	1.50			XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	-0.25			XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	-0.25				XX	XX
fr/rr	17	8.00	-780248	0.00		4.50	4.50	0.50				XX	
rr	17	9.50	-795249	0.00		5.25	5.25	1.25				XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	0.00					XX
fr/rr	18	7.00	-870247	0.00		4.00	4.00	0.00		XX			
rr	18	10.00	-810250	0.00		5.50	5.50	1.50		XX			
fr/rr	20	8.50	-085248	0.00		4.75	4.75	0.75		XX			
rr	20	10.00	-010250	0.00		5.50	5.50	1.50		XX			
	601-1414-10		7/16 closed lug kit, 10 pk (92 series)								XX	XX	
	601-1414-20		7/16 closed lug kit, 20 pk (92 series)								XX	XX	
	601-1424-10		7/16 open lug kit, 10 pk (92 series)								XX	XX	
	601-1424-20		7/16 open lug kit, 20 pk (92 series)								XX	XX	
	602-2437-10		7/16 closed lug kit, 10 pk (32, 95)							XX			XX
	602-2437-20		7/16 closed lug kit, 20 pk (32, 95)							XX			XX
78-83 Malibu 5x4.75 70.3 0-15 12mm (G Body)													

oe fr	15	6.00		15.00		4.09	2.91						
oe rr	16	6.00		15.00		4.09	2.91						
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	0.60			XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	0.71				XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	1.59				XX	
rr	15	8.00	-580248	0.00		4.50	4.50	1.59			XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	0.84			XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	0.84				XX	XX
fr/rr	17	8.00	-780248	0.00		4.50	4.50	1.59				XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	1.09				XX	XX
fr/rr	18	7.00	-870247	0.00		4.00	4.00	1.09		XX			
rr	18	8.50	-885250	17.50		5.44	4.06	1.15				XX	XX
fr/rr	20	8.50	-085248	0.00		4.75	4.75	1.84		XX			
	601-1412-10		12x1.5 closed lug kit, 10 pk (92 series)								XX	XX	
	601-1412-20		12x1.5 closed lug kit, 20 pk (92 series)								XX	XX	
	601-1422-10		12x1.5 open lug kit, 10 pk (92 series)								XX	XX	
	601-1422-20		12x1.5 open lug kit, 20 pk (92 series)								XX	XX	
	602-2439-10		12x1.5 closed lug kit, 10 pk (92 series)							XX			XX
	602-2439-20		12x1.5 closed lug kit, 20 pk (92 series)							XX			XX
62-67 Chevy II, Nova 5x4.75 70.3 0-15 7/16 (X-Body)													
oe fr	14	6.00		0.00		3.50	3.50						
oe rr	14	6.00		0.00		3.50	3.50						
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	0.00			XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	0.12				XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	1.00				XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	0.25			XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	0.25				XX	XX
fr	18	5.00	-850245	-25.40		2.00	4.00	0.50				XX	
fr/rr	18	7.00	-870247	0.00		4.00	4.00	0.50		XX			
	601-1414-10		7/16 closed lug kit, 10 pk (92 series)								XX	XX	
	601-1414-20		7/16 closed lug kit, 20 pk (92 series)								XX	XX	

	601-1424-10		7/16 open lug kit, 10 pk (92 series)							XX	XX		
	601-1424-20		7/16 open lug kit, 20 pk (92 series)							XX	XX		
	602-2437-10		7/16 closed lug kit, 10 pk (32, 95)							XX			XX
	602-2437-20		7/16 closed lug kit, 20 pk (32, 95)							XX			XX
68-74 Chevy II, Nova 5x4.75 70.3 0-15 7/16 (X-Body)													
oe fr	14	7.00		15.00		4.59	3.41						
oe rr	14	7.00		15.00		4.59	3.41						
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	0.10			XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	0.21				XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	1.09				XX	
rr	15	8.00	-580248	0.00		4.50	4.50	1.09			XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	0.34			XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	0.34				XX	XX
fr/rr	17	8.00	-780248	0.00		4.50	4.50	1.09				XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	0.59				XX	XX
fr/rr	18	7.00	-870247	0.00		4.00	4.00	0.59		XX			
rr	18	8.50	-885250	17.50		5.44	4.06	0.65				XX	XX
fr/rr	20	8.50	-085248	0.00		4.75	4.75	1.34		XX			
	601-1414-10		7/16 closed lug kit, 10 pk (92 series)								XX	XX	
	601-1414-20		7/16 closed lug kit, 20 pk (92 series)								XX	XX	
	601-1424-10		7/16 open lug kit, 10 pk (92 series)								XX	XX	
	601-1424-20		7/16 open lug kit, 20 pk (92 series)								XX	XX	
	602-2437-10		7/16 closed lug kit, 10 pk (32, 95)							XX			XX
	602-2437-20		7/16 closed lug kit, 20 pk (32, 95)							XX			XX
75-79 Chevy II, Nova 5x4.75 70.3 0-15 7/16 (X-Body)													
oe fr	14	7.00		15.00		4.59	3.41						
oe rr	14	7.00		15.00		4.59	3.41						
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	0.10			XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	0.21				XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	1.09				XX	

rr	15	8.00	-580248	0.00		4.50	4.50	1.09			XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	0.34			XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	0.34				XX	XX
fr/rr	17	8.00	-780248	0.00		4.50	4.50	1.09				XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	0.59				XX	XX
fr/rr	18	7.00	-870247	0.00		4.00	4.00	0.59		XX			
rr	18	8.50	-885250	17.50		5.44	4.06	0.65				XX	XX
fr/rr	20	8.50	-085248	0.00		4.75	4.75	1.34		XX			
*Denotes: Relocating rear shocks inboard may be required													
	601-1414-10		7/16 closed lug kit, 10 pk (92 series)								XX	XX	
	601-1414-20		7/16 closed lug kit, 20 pk (92 series)								XX	XX	
	601-1424-10		7/16 open lug kit, 10 pk (92 series)								XX	XX	
	601-1424-20		7/16 open lug kit, 20 pk (92 series)								XX	XX	
	602-2437-10		7/16 closed lug kit, 10 pk (32, 95)							XX			XX
	602-2437-20		7/16 closed lug kit, 20 pk (32, 95)							XX			XX
69-72 Monte Carlo 5x4.75 70.3 0-15 7/16 (G-Body)													
oe fr	15	7.00		0.00		4.00	4.00						
oe rr	15	7.00		0.00		4.00	4.00						
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	-0.50			XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	-0.38				XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	0.50				XX	
fr/rr	15	8.00	-580248	0.00		4.50	4.50	0.50			XX	XX	
rr	15	10.00	-510250	0.00		5.50	5.50	1.50			XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	-0.25			XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	-0.25				XX	XX
fr/rr	17	8.00	-780248	0.00		4.50	4.50	0.50				XX	
rr	17	9.50	-795249	0.00		5.25	5.25	1.25				XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	0.00				XX	
fr/rr	18	7.00	-870247	0.00		4.00	4.00	0.00		XX			
rr	18	10.00	-810250	0.00		5.50	5.50	1.50		XX			
fr/rr	20	8.50	-085248	0.00		4.75	4.75	0.75		XX			
rr	20	10.00	-010250	0.00		5.50	5.50	1.50		XX			

	601-1414-10		7/16 closed lug kit, 10 pk (92 series)								XX	XX	
	601-1414-20		7/16 closed lug kit, 20 pk (92 series)								XX	XX	
	601-1424-10		7/16 open lug kit, 10 pk (92 series)								XX	XX	
	601-1424-20		7/16 open lug kit, 20 pk (92 series)								XX	XX	
	602-2437-10		7/16 closed lug kit, 10 pk (32, 95)							XX			XX
	602-2437-20		7/16 closed lug kit, 20 pk (32, 95)							XX			XX
78-87 El Camino, Monte Carlo 5x4.75 70.3 0-15 12mm (G Body)													
oe fr	15	7.00		15.00		4.59	3.41						
oe rr	16	7.00		15.00		4.59	3.41						
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	0.10			XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	0.21				XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	1.09				XX	
rr	15	8.00	-580248	0.00		4.50	4.50	1.09			XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	0.34			XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	0.34				XX	XX
fr/rr	17	8.00	-780248	0.00		4.50	4.50	1.09				XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	0.59				XX	XX
fr/rr	18	7.00	-870247	0.00		4.00	4.00	0.59		XX			
rr	18	8.50	-885250	17.50		5.44	4.06	0.65				XX	XX
fr/rr	20	8.50	-085248	0.00		4.75	4.75	1.34		XX			
	601-1412-10		12x1.5 closed lug kit, 10 pk (92 series)								XX	XX	
	601-1412-20		12x1.5 closed lug kit, 20 pk (92 series)								XX	XX	
	601-1422-10		12x1.5 open lug kit, 10 pk (92 series)								XX	XX	
	601-1422-20		12x1.5 open lug kit, 20 pk (92 series)								XX	XX	
	602-2439-10		12x1.5 closed lug kit, 10 pk (92 series)							XX			XX
	602-2439-20		12x1.5 closed lug kit, 20 pk (92 series)							XX			XX

Race Star Wheel Applications

These are recommended fitments for O.E. vehicles.

CHEVROLET SILVERADO 1500 TRUCK ALL YEARS

71-87 C10 1500 2wd 5x5 78.1 0-15 1/2-20

oe fr/rr	15	7.00		0.00		4.00	4.00													
oe rr/rr	15	7.00		0.00		4.00	4.00													
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe				32	92	93						
rr	15	10.00	-510950	0.00		5.50	5.50	1.50					XX							
fr	17	4.50	-745942	-25.40		1.75	3.75	-0.25					XX							
fr	17	7.00	-770947	6.40		4.25	3.75	-0.25					XX							
rr	17	9.50	-795949	0.00		5.25	5.25	1.25					XX							
fr	18	7.00	-870947	0.00		4.00	4.00	0.00				XX								
fr	18	10.00	-810950	0.00		5.50	5.50	1.50				XX								
rr	20	8.50	-085248	0.00		4.75	4.75	0.75				XX								
	20	10.00	-010950	0.00		5.50	5.50	1.50				XX								
		601-1416D-10	1/2-20 closed shank lug kit, 10 pk (92)															XX		
		601-1416D-20	1/2-20 closed shank lug kit, 20 pk (92)															XX		
		601-1426D-10	1/2-20 open shank lug kit, 10 pk (92)															XX		
		601-1426D-20	1/2-20 open shank lug kit, 20 pk (92)															XX		
		602-2438-10	1/2-20 closed conical lug kit, 10 pk (32, 93)															XX		XX
		602-2438-20	1/2-20 closed conical lug kit, 20 pk (32, 93)															XX		XX

88-98 C-1500 2wd 5x5 78.1 0-15 14x1.5

												W/ mm	RATIO	DIA	OD	S/W	SW/H
oe fr/rr	15	7.00		0.00		4.00	4.00					245	45	17	25.68	9.65	4.34
oe rr/rr	15	7.00		0.00		4.00	4.00					245	45	17	25.68	9.65	4.34
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe							32	92	93
rr	15	10.00	-510950	0.00		5.50	5.50	1.50									XX
fr	17	4.50	-745942	-25.40		1.75	3.75	-0.25									XX
fr	17	7.00	-770947	6.40		4.25	3.75	-0.25									XX
rr	17	9.50	-795949	0.00		5.25	5.25	1.25									XX
fr	18	7.00	-870947	0.00		4.00	4.00	0.00							XX		
fr	18	10.00	-810950	0.00		5.50	5.50	1.50							XX		
rr	20	8.50	-085248	0.00		4.75	4.75	0.75							XX		
	20	10.00	-010950	0.00		5.50	5.50	1.50							XX		

	601-1428-10	14x1.5 closed lug kit, 10 pk (92)													XX											
	601-1428-20	14x1.5 closed lug kit, 20 pk (92)													XX											
	601-1430-10	14x1.5 open lug kit, 10 pk (92)													XX											
	601-1430-20	14x1.5 open lug kit, 20 pk (92)													XX											
	602-2428-10	14x1.5 closed lug kit, 10 pk (32)												XX		XX										
	602-2428-20	14x1.5 closed lug kit, 20 pk (32)												XX		XX										
99-04 Silverado 1500 2wd 6x5.50 78.1 15-25 14x1.5																										
oe fr/rr	16	7.00		15.00		4.59	3.41			W/ mm	RATIO	DIA	OD	S/W	SW/H											
oe rr/rr	16	7.00		15.00		4.59	3.41			235	75	16	29.88	9.25	6.94											
										255	70	16	30.06	10.04	7.03											
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe					32	92	93											
rr	15	10.00	-510853	38.00		7.00	4.00	0.59							XX											
fr	17	4.50	-745842	-25.40		1.75	3.75	0.34							XX											
fr	17	7.00	-770847	6.40		4.25	3.75	0.34							XX											
rr	17	9.50	-795852	25.00		6.23	4.27	0.86							XX											
fr/rr	20	8.50	-085949	12.00		5.22	4.28	0.87					XX													
fr/rr	20	9.00	-090851	25.00		5.98	4.02	0.61							XX											
rr	20	10.00	-010950	25.00		6.48	4.52	1.11					XX													
	602-2428-12	14x1.5 closed lug kit, 12 pk (32,93)													XX		XX									
	602-2428-24	14x1.5 closed lug kit, 24 pk (32,93)													XX		XX									
05-06 Silverado 1500 2wd 6x5.50 78.1 15-25 14x1.5																										
oe fr/rr	17	7.50		31.00		5.47	3.03			W/ mm	RATIO	DIA	OD	S/W	SW/H											
oe rr/rr	20	8.50		22.00		5.62	3.88			245	70	17	30.50	9.65	6.75											
										275	55	20	31.91	10.83	5.95											
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe					32	92	93											
rr	15	10.00	-510853	38.00		7.00	4.00	0.12							XX											
fr	17	4.50	-745842	-25.40		1.75	3.75	0.72							XX											
fr	17	7.00	-770847	6.40		4.25	3.75	0.72							XX											
rr	17	9.50	-795852	25.00		6.23	4.27	0.38							XX											
fr/rr	20	8.50	-085949	12.00		5.22	4.28	0.39					XX													
fr/rr	20	9.00	-090851	25.00		5.98	4.02	0.13							XX											
rr	20	10.00	-010950	30.00		6.68	4.32	0.44					XX													
	602-2428-12	14x1.5 closed lug kit, 12 pk (32,93)													XX		XX									
	602-2428-24	14x1.5 closed lug kit, 24 pk (32,93)													XX		XX									
07-13 Silverado 1500 2wd 6x5.50 78.1 15-25 14x1.5																										
oe fr/rr	17	7.50		15.00		4.84	3.66			W/ mm	RATIO	DIA	OD	S/W	SW/H											
										245	70	17	30.50	9.65	6.75											

oe fr/rr	18	8.00		25.00		5.48	3.52		265	65	18	31.56	10.43	6.78	
oe rr/rr	20	8.50		31.00		5.97	3.53		275	55	20	31.91	10.83	5.95	
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe				32	92	93	
rr	15	10.00	-510853	38.00		7.00	4.00	0.47						XX	
fr	17	4.50	-745842	-25.40		1.75	3.75	0.09						XX	
fr	17	7.00	-770847	6.40		4.25	3.75	0.09						XX	
rr	17	9.50	-795852	25.00		6.23	4.27	0.74						XX	
fr/rr	20	8.50	-085949	12.00		5.22	4.28	0.75				XX			
fr/rr	20	9.00	-090851	25.00		5.98	4.02	0.49						XX	
rr	20	10.00	-010950	30.00		6.68	4.32	0.79				XX			
	602-2428-12		14x1.5 closed lug kit, 12 pk (32,93)									XX		XX	
	602-2428-24		14x1.5 closed lug kit, 24 pk (32,93)									XX		XX	
14-up Silverado 1500 PU 15-35 6x5.50 14x1.5 78.1id 30.5										W/ mm	RATIO	DIA	OD	S/W	SW/H
oe fr/rr	17	7.50		15.00		4.84	3.66		255	70	17	31.06	10.04	7.03	
oe fr/rr	18	8.00		25.00		5.48	3.52		265	65	18	31.56	10.43	6.78	
oe rr/rr	20	8.50		31.00		5.97	3.53		275	55	20	31.91	10.83	5.95	
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe				32	92	93	
rr	15	10.00	-510853	38.00		7.00	4.00	0.47						XX	
fr	17	4.50	-745842	-25.40		1.75	3.75	0.09						XX	
fr	17	7.00	-770847	6.40		4.25	3.75	0.09						XX	
rr	17	9.50	-795852	25.00		6.23	4.27	0.74						XX	
fr/rr	20	8.50	-085949	12.00		5.22	4.28	0.75				XX			
fr/rr	20	9.00	-090851	25.00		5.98	4.02	0.49						XX	
rr	20	10.00	-010950	30.00		6.68	4.32	0.79				XX			
	602-2428-12		14x1.5 closed lug kit, 12 pk (32,93)									XX		XX	
	602-2428-24		14x1.5 closed lug kit, 24 pk (32,93)									XX		XX	
82-04 S10 2wd Truck/ Blazer 0-15 5x4.75 12x1.5 78.1id										W/ mm	RATIO	DIA	OD	S/W	SW/H
oe fr/rr	15	7.00		0.00		4.00	4.00		255	70	17	31.06	10.04	7.03	
oe rr/rr	16	8.00		6.40		4.75	4.25		275	55	20	31.91	10.83	5.95	
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe				32	92	93	
fr	15	3.75	-537240	-28.70		1.25	3.50	-0.50						XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	-0.38						XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	0.50						XX	
fr/rr	15	8.00	-580248	0.00		4.50	4.50	0.50						XX	
rr	15	10.00	-510250	0.00		5.50	5.50	1.00						XX	
fr	17	4.50	-745842	-25.40		1.75	3.75	-0.50						XX	
fr	17	7.00	-770847	6.40		4.25	3.75	-0.50						XX	

fr/rr	17	8.00	-780248	0.00		4.50	4.50	0.25					XX	
rr	17	9.50	-795852	25.00		6.23	4.27	0.02					XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	-0.25					XX	
fr	18	7.00	-870247	0.00		4.00	4.00	-0.25					XX	XX
rr	18	10.00	-810250	0.00		5.50	5.50	1.25					XX	XX
fr/rr	20	8.50	-085248	12.00		5.22	4.28	0.03					XX	
rr	20	9.00	-095251	22.00		5.87	4.13	-0.11					XX	
rr	20	10.00	-010950	0.00		5.50	5.50	1.25					XX	
	601-1412-10		12x1.5 closed lug kit, 10 pk (92)										XX	
	601-1412-20		12x1.5 closed lug kit, 20 pk (92)										XX	
	601-1422-10		12x1.5 open lug kit, 10 pk (92)										XX	
	601-1422-20		12x1.5 open lug kit, 20 pk (92)										XX	
	602-2439-10		12x1.5 closed lug kit, 10 pk (92)										XX	
	602-2439-20		12x1.5 closed lug kit, 20 pk (92)										XX	

Race Star Wheel Applications

These are recommended fitments for O.E. vehicles.

CHEVROLET CORVETTE C3 68-82

68-82 Corvette 5x4.75 70.3 0-15 7/16 27"OD

oe fr	15	8.00		-12.60		4.00	5.00							
oe rr	15	8.00		-12.60		4.00	5.00							
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		<i>F1</i>	<i>32</i>	<i>82</i>	<i>92</i>	<i>95</i>
fr	15	3.75	-537240	-28.70		1.25	3.50	-1.49				XX	XX	
fr	15	5.00	-550244	-15.80		2.38	3.62	-1.37					XX	
fr	15	7.00	-570246	-12.70		3.50	4.50	-0.50					XX	
fr/rr	15	8.00	-580247	-12.70		4.00	5.00	0.00					XX	
rr**	15	10.00	-510248	-25.40		4.50	6.50	1.50				XX	XX	
rr**	15	10.00	-510250	0.00		5.50	5.50	0.50				XX	XX	
fr	17	4.50	-745242	-25.40		1.75	3.75	-1.25				XX	XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	-1.25					XX	XX
fr/rr	17	8.00	-780248	0.00		4.50	4.50	-0.50					XX	
rr**	17	9.50	-795249	0.00		5.25	5.25	0.25					XX	
fr	18	5.00	-850245	-25.40		2.00	4.00	-1.00					XX	XX
fr	18	7.00	-870247	0.00		4.00	4.00	-1.00			XX			
rr**	18	10.00	-810250	0.00		5.50	5.50	0.50			XX			
fr/rr	20	8.50	-085248	0.00		4.75	4.75	-0.25			XX			
rr**	20	10.00	-000250	0.00		5.50	5.50	0.50			XX			
		601-1414-10	7/16 closed lug kit, 10 pk									XX	XX	
		601-1414-20	7/16 closed lug kit, 20 pk									XX	XX	
		601-1424-10	7/16 open lug kit, 10 pk									XX	XX	
		601-1424-20	7/16 open lug kit, 20 pk									XX	XX	
		602-2437-10	7/16 closed lug kit, 10 pk								XX			XX
		602-2437-20	7/16 closed lug kit, 20 pk								XX			XX

CHEVROLET CORVETTE C4 84-96

84-88 Corvette C4 BASE 5x4.75 70.3 32-38 12mm 26"OD

oe fr	16	8.50		32.00		6.01	3.49			W/ mm	RATIO	DIA	OD	S/W	SW/H
oe rr	16	9.50		38.00		6.75	3.75			255	50	16	26.04	10.04	5.02
										255	50	16	26.04	10.04	5.02
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		<i>F1</i>	<i>32</i>	<i>82</i>	<i>92</i>	<i>95</i>	
FR	15	3.75	-537240	-28.7		1.25	3.50	0.01				XX	XX		
FR	15	5.00	-550244	-15.8		2.38	3.62	0.13					XX		

RR	15	10.00	-510254	44		7.23	3.77	0.01		XX		XX	XX	XX
FR	17	4.50	-745242	-25.4		1.75	3.75	0.26				XX	XX	XX
FR	17	4.50	-745245	-12		2.28	3.22	-0.27		XX			XX	XX
FR	17	7.00	-770247	6.4		4.25	3.75	0.26					XX	XX
RR	17	9.5	-795252	19	26	6.27	4.23	0.47					XX	
RR	17	10.5	-705253	32	38	7.25	4.25	0.50					XX	
FR	18	5.00	-850245	-25.4		2.00	4.00	0.51					XX	XX
FR	18	8.50	-885250	17.5		5.44	4.06	0.57					XX	XX
RR	18	10.5	-805253	32	38	7.25	4.25	0.50					XX	
		601-1412-10	12x1.5 closed lug kit, 10 pk (92 series)											
		601-1412-20	12x1.5 closed lug kit, 20 pk (92 series)											
													XX	XX
		601-1422-10	12x1.5 open lug kit, 10 pk (92 series)											
		601-1422-20	12x1.5 open lug kit, 20 pk (92 series)											
													XX	XX
		602-2439-10	12x1.5 closed lug kit, 10 pk (95 series)											
		602-2439-20	12x1.5 closed lug kit, 20 pk (95 series)											
										XX				XX
										XX				XX
89-92 Corvette C4 BASE 5x4.75 70.3 50 12mm 26"OD														
									W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	17	9.5		50		7.22	3.28		275	40	17	25.66	10.83	4.33
RR	17	9.5		50		7.22	3.28		275	40	17	25.66	10.83	4.33
		<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>	<i>F1</i>	<i>32</i>	<i>82</i>	<i>92</i>	<i>95</i>
FR	15	3.75	-537240	-28.7		1.25	3.50	0.22				XX	XX	
FR	15	5.00	-550244	-15.8		2.38	3.62	0.34						
RR	15	10.00	-510254	44		7.23	3.77	0.49		XX		XX	XX	XX
FR	17	4.50	-745242	-25.4		1.75	3.75	0.47				XX	XX	XX
FR	17	4.50	-745245	-12.6		2.25	3.25	-0.04		XX			XX	XX
FR	17	7.00	-770247	6.4		4.25	3.75	0.47					XX	XX
FR/RR	17	9.50	-795253	43		6.94	3.56	0.28					XX	
RR	17	10.5	-705253	32	50	7.72	3.78	0.50					XX	
FR	18	5.00	-850245	-6		2.76	3.24	-0.05					XX	XX
FR	18	8.50	-885250	17.5	25.4	5.75	3.75	0.47					XX	
RR	18	10.5	-805255	52		7.80	3.70	0.42					XX	XX
		601-1412-10	12x1.5 closed lug kit, 10 pk (92 series)											
		601-1412-20	12x1.5 closed lug kit, 20 pk (92 series)											
													XX	XX
		601-1422-10	12x1.5 open lug kit, 10 pk (92 series)											
		601-1422-20	12x1.5 open lug kit, 20 pk (92 series)											
													XX	XX
		602-2439-10	12x1.5 closed lug kit, 10 pk (95 series)											
										XX				XX

	602-2439-20	12x1.5 closed lug kit, 20 pk (95 series)								XX				XX
93-96 Corvette C4 BASE 5x4.75 70.3 50 12mm 26"OD														
									W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	17	8.5		50		6.72	2.78		255	45	17	26.04	10.04	4.52
RR	17	9.5		50		7.22	3.28		275	40	17	25.66	10.83	4.33
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		F1	32	82	92	95
FR	15	3.75	-537240	-28.7	-22.7	1.48	3.27	0.49				XX	XX	
FR	15	5.00	-550244	-15.8	-7	2.72	3.28	0.49					XX	
RR	15	10.00	-510254	44		7.23	3.77	0.49		XX			XX	XX
FR	17	4.50	-745242	-25.4	-12.6	2.25	3.25	0.46				XX	XX	
FR	17	4.50	-745245	-12		2.28	3.22	0.44		XX			XX	XX
FR	17	7.00	-770249	22		4.87	3.13	0.35					XX	XX
FR	17	8.00	-780250	25.4	32	5.76	3.24	0.46					XX	
RR	17	9.5	-795253	43.5		6.96	3.54	0.26					XX	
RR	17	10.5	-705253	32	50	7.72	3.78	0.50					XX	
FR	18	5.00	-850246	-6		2.76	3.24	0.45						XX
FR	18	8.50	-885250	17.5	38	6.25	3.25	0.47					XX	
RR	18	10.5	-805255	52		7.80	3.70	0.42					XX	XX
	601-1412-10	12x1.5 closed lug kit, 10 pk (92 series)										XX	XX	
	601-1412-20	12x1.5 closed lug kit, 20 pk (92 series)										XX	XX	
	601-1422-10	12x1.5 open lug kit, 10 pk (92 series)										XX	XX	
	601-1422-20	12x1.5 open lug kit, 20 pk (92 series)										XX	XX	
	602-2439-10	12x1.5 closed lug kit, 10 pk (95 series)								XX				XX
	602-2439-20	12x1.5 closed lug kit, 20 pk (95 series)								XX				XX
93-95 Corvette Z07 C4 BASE 5x4.75 70.3 50 12mm 26"OD														
									W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	17	9.5		50		7.22	3.28		275	40	17	25.66	10.83	4.33
RR	17	9.5		50		7.22	3.28		275	40	17	25.66	10.83	4.33
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		F1	32	82	92	95
RR	15	10.00	-510254	44		7.23	3.77	0.49		XX		XX	XX	XX
FR	17	4.50	-745242	-25.4		1.75	3.75	0.47				XX	XX	XX
FR	17	4.50	-745245	-12		2.28	3.22	-0.06		XX			XX	XX
FR	17	7.00	-770247	6.4		4.25	3.75	0.47					XX	XX
FR	17	7.00	-770249	22		4.87	3.13	-0.15					XX	XX
FR/RR	17	9.50	-795253	43.5		6.96	3.54	0.26					XX	
RR	17	10.5	-705253	32	50	7.72	3.78	0.50					XX	
FR	18	5.00	-850246	-6		2.76	3.24	-0.05					XX	XX
FR	18	8.50	-885250	17.5	25	5.73	3.77	0.48					XX	XX
RR	18	10.5	-805255	52		7.80	3.70	0.42					XX	XX

	601-1412-10											XX	XX		
	601-1412-20											XX	XX		
	601-1422-10											XX	XX		
	601-1422-20											XX	XX		
	602-2439-10									XX				XX	
	602-2439-20									XX				XX	
96 Corvette Z16 CONV C4 5x4.75 70.3 50 12mm 26" OD										W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	17	8.5		50		6.72	2.78			255	45	17	26.04	10.04	4.52
RR	17	9.5		50		7.22	3.28			285	40	17	25.98	11.22	4.49
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		<i>F1</i>	<i>32</i>	<i>82</i>	<i>92</i>	<i>95</i>	
RR	15	10.00	-510254	44		7.23	3.77	0.49		XX		XX	XX	XX	
FR	17	4.50	-745242	-25.4	-12.6	2.25	3.25	0.46				XX	XX	XX	
FR	17	4.50	-745245	-12		2.28	3.22	0.44		XX			XX	XX	
FR	17	7.00	-770249	22		4.87	3.13	0.35					XX	XX	
RR	17	9.5	-795253	43.5		6.96	3.54	0.26					XX		
RR	17	10.5	-705253	32	50	7.72	3.78	0.50					XX		
FR	18	5.00	-850246	-6		2.76	3.24	0.45					XX	XX	
FR	18	8.50	-885253	50		6.72	2.78	0.00					XX	XX	
RR	18	10.5	-805255	52		7.80	3.70	0.42					XX	XX	
	601-1412-10												XX	XX	
	601-1412-20												XX	XX	
	601-1422-10												XX	XX	
	601-1422-20												XX	XX	
	602-2439-10									XX					XX
	602-2439-20									XX					XX
96 Corvette Z16 COUPE C4 5x4.75 70.3 36-50 12mm 26" OD										W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	17	9.5		50		7.22	3.28			275	40	17	25.66	10.83	4.33
RR	17	11		36		7.42	4.58			315	35	17	25.68	12.40	4.34
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		<i>F1</i>	<i>32</i>	<i>82</i>	<i>92</i>	<i>95</i>	
RR	15	10.00	-510254	44		7.23	3.77	0.49		XX		XX	XX	XX	
FR	17	4.50	-745242	-25.4		1.75	3.75	0.47				XX	XX	XX	
FR	17	4.50	-745245	-12.7		2.25	3.25	-0.03		XX			XX	XX	
FR	17	7.00	-770247	6.4		4.25	3.75	0.47					XX	XX	
RR	17	9.5	-795249	0	6	5.49	5.01	0.43					XX		

RR	17	10.5	-705253	32		7.01	4.49	-0.09					XX	XX	
FR	18	5.00	-850246	-6		2.76	3.24	-0.05					XX	XX	
FR	18	8.50	-885253	17.5	25	5.73	3.77	0.48					XX		
RR	18	10.5	-805253	32		7.01	4.49	-0.09					XX	XX	
	601-1412-10		12x1.5 closed lug kit, 10 pk (92 series)										XX	XX	
	601-1412-20		12x1.5 closed lug kit, 20 pk (92 series)										XX	XX	
	601-1422-10		12x1.5 open lug kit, 10 pk (92 series)										XX	XX	
	601-1422-20		12x1.5 open lug kit, 20 pk (92 series)										XX	XX	
	602-2439-10		12x1.5 closed lug kit, 10 pk (95 series)							XX				XX	
	602-2439-20		12x1.5 closed lug kit, 20 pk (95 series)							XX				XX	
85-87 Corvette Z51 C4 5x4.75 70.3 38 12mm 26"OD										W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	16	9.5		38		6.75	3.75			255	50	16	26.04	10.04	5.02
RR	16	9.5		38		6.75	3.75			255	50	16	26.04	10.04	5.02
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		<i>F1</i>	32	82	92	95	
RR	15	10.00	-510254	44		7.23	3.77	0.01		XX		XX	XX	XX	
FR	17	4.50	-745242	-25.4		1.75	3.75	0.00				XX	XX	XX	
FR	17	7.00	-770247	6.4		4.25	3.75	-0.01					XX	XX	
FR	17	8.00	-780248	0	13	5.01	3.99	0.23					XX		
RR	17	9.5	-795252	19	26	6.27	4.23	0.47					XX		
RR	17	10.5	-705253	32	38	7.25	4.25	0.50					XX		
FR	18	5.00	-850245	-25.4		2.00	4.00	0.25					XX	XX	
FR	18	8.5	-885250	17.5		5.44	4.06	0.31					XX	XX	
RR	18	10.5	-805253	32	38	7.25	4.25	0.50					XX		
	601-1412-10		12x1.5 closed lug kit, 10 pk (92 series)										XX	XX	
	601-1412-20		12x1.5 closed lug kit, 20 pk (92 series)										XX	XX	
	601-1422-10		12x1.5 open lug kit, 10 pk (92 series)										XX	XX	
	601-1422-20		12x1.5 open lug kit, 20 pk (92 series)										XX	XX	
	602-2439-10		12x1.5 closed lug kit, 10 pk (95 series)							XX				XX	
	602-2439-20		12x1.5 closed lug kit, 20 pk (95 series)							XX				XX	
88 Corvette Z51 C4 5x4.75 70.3 56 12mm 26"OD										W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	17	9.5		56		7.45	3.05			275	40	17	25.66	10.83	4.33
RR	17	9.5		56		7.45	3.05			275	40	17	25.66	10.83	4.33
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		<i>F1</i>	32	82	92	95	
RR	15	10.00	-510254	44	50	7.47	3.53	-0.47					XX	XX	

88 Corvette Z52 C4 5x4.75 70.3 56 12mm 26"OD									W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	17	9.5		56		7.45	3.05		275	40	17	25.66	10.83	4.33
RR	17	9.5		56		7.45	3.05		275	40	17	25.66	10.83	4.33
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		<i>F1</i>	<i>32</i>	<i>82</i>	<i>92</i>	<i>95</i>
RR	15	10.00	-510254	44	50	7.47	3.53	0.30				XX	XX	
FR	17	4.50	-745245	-12		2.28	3.22	0.18		XX			XX	XX
FR	17	7.00	-770249	22		4.87	3.13	0.09					XX	XX
FR	17	8.00	-780250	25.4		5.50	3.50	0.45					XX	
FR/RR	17	9.50	-795253	43.5		6.96	3.54	0.49					XX	
RR	17	10.5	-705253	32	57	7.99	3.51	0.46					XX	
FR	18	5.00	-850245	-6		2.76	3.24	-0.30					XX	XX
FR	18	8.50	-885250	50		6.72	2.78	-0.75					XX	XX
RR	18	10.5	-805255	52	57	7.99	3.51	0.46					XX	
	601-1412-10		12x1.5 closed lug kit, 10 pk (92 series)										XX	XX
	601-1412-20		12x1.5 closed lug kit, 20 pk (92 series)										XX	XX
	601-1422-10		12x1.5 open lug kit, 10 pk (92 series)										XX	XX
	601-1422-20		12x1.5 open lug kit, 20 pk (92 series)										XX	XX
	602-2439-10		12x1.5 closed lug kit, 10 pk (95 series)							XX				XX
	602-2439-20		12x1.5 closed lug kit, 20 pk (95 series)							XX				XX
90-95 Corvette ZR1 C4 5x4.75 70.3 36-50 12mm 26"OD									W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	17	9.5		50		7.22	3.28		275	40	17	25.66	10.83	4.33
RR	17	11		36		7.42	4.58		315	35	17	25.68	12.40	4.34
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		<i>F1</i>	<i>32</i>	<i>82</i>	<i>92</i>	<i>95</i>
RR	15	10.00	-510254	44		7.23	3.77	-0.81		XX		XX	XX	XX
FR	17	4.50	-745242	-25.4		1.75	3.75	0.47				XX	XX	XX
FR	17	4.50	-745245	-12.7		2.25	3.25	-0.03		XX			XX	XX
FR	17	7.00	-770247	6.4		4.25	3.75	0.47					XX	XX
FR	17	9.50	-795253	43.5		6.96	3.54	0.26					XX	
RR	17	10.5	-705253	32		7.01	4.49	-0.09					XX	XX
FR	18	5.00	-850246	-6		2.76	3.24	-0.05					XX	XX
FR	18	8.50	-885253	17.5	25	5.73	3.77	0.48					XX	
RR	18	10.5	-805253	32		7.01	4.49	-0.09					XX	XX
	601-1412-10		12x1.5 closed lug kit, 10 pk (92 series)										XX	XX
	601-1412-20		12x1.5 closed lug kit, 20 pk (92 series)										XX	XX
	601-1422-10		12x1.5 open lug kit, 10 pk (92 series)										XX	XX

	601-1422-20	12x1.5 open lug kit, 20 pk (92 series)									XX	XX			
	602-2439-10	12x1.5 closed lug kit, 10 pk (95 series)							XX				XX		
	602-2439-20	12x1.5 closed lug kit, 20 pk (95 series)							XX				XX		
CHEVROLET CORVETTE C5 97-04															
97-01 Corvette C5 BASE 5x4.75 70.3 56-65 12mm 26"OD										W/ mm	RATIO	DIA	OD	S/W	SW/H
oe fr	17	8.50		56.00		6.95	2.55		245	45	17	25.68	9.65	4.34	
oe rr	18	9.50		61.00		7.65	2.85		275	40	18	26.66	10.83	4.33	
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		F1	32	82	92	95	
RR	15	10.00	-510254	44	56	7.70	3.30	0.45					XX		
FR	17	4.50	-745245	-12	-6	2.51	2.99	0.14					XX		
FR	17	7.00	-770249	22	26	5.02	2.98	0.13					XX		
RR	17	9.5	-795253	43.5	49	7.18	3.32	0.47					XX		
RR	17	10.5	-705253	32	62	8.19	3.31	0.46					XX		
FR	18	5.00	-850246	-6	0	3.00	3.00	-0.30					XX		
FR	18	8.50	-885253	50		6.72	2.78	-0.51					XX		
RR	18	10.5	-805255	52	62	8.19	3.31	0.76					XX		
	601-1412-10	12x1.5 closed lug kit, 10 pk (92 series)											XX		
	601-1412-20	12x1.5 closed lug kit, 20 pk (92 series)											XX		
	601-1422-10	12x1.5 open lug kit, 10 pk (92 series)											XX		
	601-1422-20	12x1.5 open lug kit, 20 pk (92 series)											XX		
02-04 Corvette C5 BASE 5x4.75 70.3 58-65 12mm 26"OD										W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	17	8.5		58		7.03	2.47		245	45	17	25.68	9.65	4.34	
RR	18	9.5		65		7.81	2.69		275	40	18	26.66	10.83	4.33	
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		F1	32	82	92	95	
RR	15	10.00	-510254	44	58	7.78	3.22	0.53					XX		
FR	17	4.50	-745245	-12	-4	2.59	2.91	0.44					XX		
FR	17	7.00	-770249	22	26	5.02	2.98	0.51					XX		
FR	17	8.00	-780250	25.4	39	6.04	2.96	0.50					XX		
RR	17	9.5	-795254	52		7.30	3.20	0.51					XX		
RR	17	10.5	-705253	32	65	8.31	3.19	0.50					XX		
FR	18	5.00	-850247	0		3.00	3.00	0.53					XX	XX	
FR	18	8.50	-885253	50		6.72	2.78	0.31					XX		
RR	18	10.5	-805257	76		8.74	2.76	0.29					XX	XX	
	601-1412-10	12x1.5 closed lug kit, 10 pk (92 series)											XX		

	601-1412-20	12x1.5 closed lug kit, 20 pk (92 series)											XX		
	601-1422-10	12x1.5 open lug kit, 10 pk (92 series)											XX		
	601-1422-20	12x1.5 open lug kit, 20 pk (92 series)											XX		
	602-2439-10	12x1.5 closed lug kit, 10 pk (95 series)												XX	
	602-2439-20	12x1.5 closed lug kit, 20 pk (95 series)												XX	
01-04 Corvette C5 Z06 5x4.75 70.3 58-65 12mm 26"OD										W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	17	9.5		54		7.38	3.12			265	40	17	25.35	10.43	4.17
RR	18	10.5		58		8.03	3.47			295	35	18	26.13	11.61	4.06
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		F1	32	82	92	95	
FR	17	4.50	-745245	-12.7		2.25	3.25	0.13		XX				XX	XX
FR	17	7.00	-770249	22		4.87	3.13	0.01						XX	XX
RR	17	9.5	-795252	19	38	6.75	3.75	0.29						XX	
RR	17	10.5	-705253	32	51	7.76	3.74	0.28						XX	
FR	18	5.00	-850246	-6		2.76	3.24	0.11						XX	XX
FR	18	8.50	-885250	17.5	29	5.89	3.61	0.48						XX	
RR	18	10.5	-805255	52		7.80	3.70	0.24						XX	XX
	601-1412-10	12x1.5 closed lug kit, 10 pk (92 series)												XX	
	601-1412-20	12x1.5 closed lug kit, 20 pk (92 series)												XX	
	601-1422-10	12x1.5 open lug kit, 10 pk (92 series)												XX	
	601-1422-20	12x1.5 open lug kit, 20 pk (92 series)												XX	
	602-2439-10	12x1.5 closed lug kit, 10 pk (95 series)								XX					XX
	602-2439-20	12x1.5 closed lug kit, 20 pk (95 series)								XX					XX
CHEVROLET CORVETTE C6 05-13															
05-13 Corvette C6 BASE 5x4.75 70.3 56-79 12mm 26"OD										W/ mm	RATIO	DIA	OD	S/W	SW/H
oe fr	18	8.50		56.00		6.95	2.55			245	40	18	25.72	9.65	3.86
oe rr	19	10.00		79.00		8.61	2.39			285	35	19	26.85	11.22	3.93
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		F1	32	82	92	95	
FR	17	4.50	-745245	-12.00		2.28	3.22	0.68		XX				XX	XX
FR	17	7.00	-770249	22.00		4.87	3.13	0.59						XX	XX
RR	17	9.50	-795254	52.00		7.30	3.20	0.81						XX	
FR	18	5.00	-850246	-6.00		2.76	3.24	0.69						XX	XX
FR	18	8.50	-885253	50.00		6.72	2.78	0.24						XX	
RR	18	10.50	-805257	76.00		8.74	2.76	0.37						XX	XX

	601-1412-10													XX	
	601-1412-20													XX	
	601-1422-10													XX	
	601-1422-20													XX	
	602-2439-10									XX				XX	
	602-2439-20									XX				XX	
05-09 Corvette C6 Z51 5x4.75 70.3 56-79 12mm 26" OD										W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	18	8.5		56		6.95	2.55			245	40	18	25.72	9.65	3.86
RR	19	10		79		8.61	2.39			285	35	19	26.85	11.22	3.93
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		<i>F1</i>	<i>32</i>	<i>82</i>	<i>92</i>	<i>95</i>	
FR	17	4.50	-745245	-12	-6	2.51	2.99	0.44						XX	
FR	17	7.00	-770249	22	26	5.02	2.98	0.43						XX	
FR	18	5.00	-850246	-6	0	3.00	3.00	0.45						XX	
FR	18	8.50	-885253	50		6.72	2.78	0.24						XX	
RR	18	10.5	-805257	76		8.74	2.76	0.37						XX	XX
	601-1412-10														XX
	601-1412-20														XX
	601-1422-10														XX
	601-1422-20														XX
	602-2439-10														XX
	602-2439-20														XX
06-13 Corvette C6 Z06 5x4.75 70.3 40-59 12mm 26" OD										W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	18	9.5		40		6.82	3.68			275	35	18	25.58	10.83	3.79
RR	19	12		59		8.82	4.18			325	30	19	26.68	12.80	3.84
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		<i>F1</i>	<i>32</i>	<i>82</i>	<i>92</i>	<i>95</i>	
FR	17	4.50	-745242	-25.4		1.75	3.75	0.07						XX	XX
FR	17	7.00	-770247	6.4		4.25	3.75	0.07						XX	XX
FR	17	9.50	-795252	19	32	6.51	3.99	0.31							
RR	17	9.5	-795252	19		6.00	4.50	0.32							
RR	17	10.5	-705253	32		7.01	4.49	0.31						XX	XX
FR	18	5.00	-850245	-25.4		2.00	4.00	0.32						XX	XX
FR	18	8.50	-885250	17.5		5.44	4.06	0.39						XX	XX
RR	18	10.5	-805253	32		7.01	4.49	0.31						XX	XX

	601-1412-10	12x1.5 closed lug kit, 10 pk (92 series)											XX		
	601-1412-20	12x1.5 closed lug kit, 20 pk (92 series)											XX		
	601-1422-10	12x1.5 open lug kit, 10 pk (92 series)											XX		
	601-1422-20	12x1.5 open lug kit, 20 pk (92 series)											XX		
	602-2439-10	12x1.5 closed lug kit, 10 pk (95 series)												XX	
	602-2439-20	12x1.5 closed lug kit, 20 pk (95 series)												XX	
09-13 Corvette C6 ZR1 5x4.75 70.3 40-59 12mm 26"OD										W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	19	10		40		7.07	3.93			285	30	19	25.73	11.22	3.37
RR	20	12		59		8.82	4.18			335	25	20	26.59	13.19	3.30
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		F1	32	82	92	95	
FR	17	4.50	-745242	-25.4		1.75	3.75	-0.18						XX	XX
FR	17	7.00	-770247	6.4		4.25	3.75	-0.18						XX	XX
FR	17	9.50	-795252	19		6.00	4.50	0.58						XX	
RR	17	10.5	-705253	32		7.01	4.49	0.31						XX	XX
FR	18	5.00	-850245	-25.4		2.00	4.00	0.07						XX	XX
FR	18	8.50	-885250	17.5		5.44	4.06	0.14						XX	XX
RR	18	10.5	-805253	32		7.01	4.49	0.31						XX	XX
	601-1412-10	12x1.5 closed lug kit, 10 pk (92 series)												XX	
	601-1412-20	12x1.5 closed lug kit, 20 pk (92 series)												XX	
	601-1422-10	12x1.5 open lug kit, 10 pk (92 series)												XX	
	601-1422-20	12x1.5 open lug kit, 20 pk (92 series)												XX	
	602-2439-10	12x1.5 closed lug kit, 10 pk (95 series)													XX
	602-2439-20	12x1.5 closed lug kit, 20 pk (95 series)													XX
10-13 Corvette C6 GS 5x4.75 70.3 40-59 12mm 26"OD										W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	18	9.5		40		6.82	3.68			245	40	18	25.72	9.65	3.86
RR	19	12		59		8.82	4.18			285	35	19	26.85	11.22	3.93
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		F1	32	82	92	95	
FR	17	4.50	-745242	-25.4		1.75	3.75	0.07						XX	XX
FR	17	7.00	-770247	6.4		4.25	3.75	0.07						XX	XX
FR	17	9.50	-795252	19	27	6.31	4.19	0.51						XX	
RR	17	10.5	-705253	32		7.01	4.49	0.31						XX	XX
FR	18	5.00	-850245	-25.4		2.00	4.00	-0.18						XX	XX
FR	18	8.50	-885250	17.5		5.44	4.06	-0.12						XX	XX
RR	18	10.5	-805253	32		7.01	4.49	0.31						XX	XX

	601-1412-10	12x1.5 closed lug kit, 10 pk (92 series)											XX			
	601-1412-20	12x1.5 closed lug kit, 20 pk (92 series)											XX			
	601-1422-10	12x1.5 open lug kit, 10 pk (92 series)											XX			
	601-1422-20	12x1.5 open lug kit, 20 pk (92 series)											XX			
	602-2439-10	12x1.5 closed lug kit, 10 pk (95 series)												XX		
	602-2439-20	12x1.5 closed lug kit, 20 pk (95 series)												XX		
12-13 Corvette C6 PDE (ZR1) 5x4.75 70.3 40-59 12mm 26"OD											W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	18	9.5		40		6.82	3.68			245	40	18	25.72	9.65	3.86	
RR	19	12		59		8.82	4.18			285	35	19	26.85	11.22	3.93	
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		F1	32	82	92	95		
FR	17	4.50	-745242	-25.4		1.75	3.75	0.07						XX	XX	
FR	17	7.00	-770247	6.4		4.25	3.75	0.07						XX	XX	
FR	17	9.50	-795252	19	27	6.31	4.19	0.51						XX		
RR	17	10.5	-705253	32		7.01	4.49	0.31						XX	XX	
FR	18	5.00	-850245	-25.4		2.00	4.00	-0.18						XX	XX	
FR	18	8.50	-885250	17.5		5.44	4.06	-0.12						XX	XX	
RR	18	10.5	-805253	32		7.01	4.49	0.31						XX	XX	
	601-1412-10	12x1.5 closed lug kit, 10 pk (92 series)												XX		
	601-1412-20	12x1.5 closed lug kit, 20 pk (92 series)												XX		
	601-1422-10	12x1.5 open lug kit, 10 pk (92 series)												XX		
	601-1422-20	12x1.5 open lug kit, 20 pk (92 series)												XX		
	602-2439-10	12x1.5 closed lug kit, 10 pk (95 series)													XX	
	602-2439-20	12x1.5 closed lug kit, 20 pk (95 series)													XX	
12-13 Corvette C6 207 5x4.75 70.3 40-59 12mm 26"OD											W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	19	10		40		7.07	3.93			285	30	19	25.73	11.22	3.37	
RR	20	12		59		8.82	4.18			335	25	20	26.59	13.19	3.30	
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		F1	32	82	92	95		
FR	17	4.50	-745242	-25.4		1.75	3.75	-0.18						XX	XX	
FR	17	7.00	-770247	6.4		4.25	3.75	-0.18						XX	XX	
FR	17	9.50	-795252	19	27	6.31	4.19	0.26						XX		
RR	17	10.5	-705253	32		7.01	4.49	0.31						XX	XX	
FR	18	5.00	-850245	-25.4		2.00	4.00	-0.18						XX	XX	
FR	18	8.50	-885250	17.5		5.44	4.06	-0.12						XX	XX	
RR	18	10.5	-805253	32		7.01	4.49	0.31						XX	XX	

	601-1412-10	12x1.5 closed lug kit, 10 pk (92 series)											XX			
	601-1412-20	12x1.5 closed lug kit, 20 pk (92 series)											XX			
	601-1422-10	12x1.5 open lug kit, 10 pk (92 series)											XX			
	601-1422-20	12x1.5 open lug kit, 20 pk (92 series)											XX			
	602-2439-10	12x1.5 closed lug kit, 10 pk (95 series)												XX		
	602-2439-20	12x1.5 closed lug kit, 20 pk (95 series)												XX		
13 Corvette C6 427 5x4.75 70.3 40-59 12mm 26"OD											W/ mm	RATIO	DIA	OD	S/W	SW/H
FR	19	10		40		7.07	3.93			285	30	19	25.73	11.22	3.37	
RR	20	12		59		8.82	4.18			335	25	20	26.59	13.19	3.30	
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		F1	32	82	92	95		
FR	17	4.50	-745242	-25.4		1.75	3.75	3.75						XX	XX	
FR	17	7.00	-770247	6.4		4.25	3.75	3.75						XX	XX	
FR	17	9.50	-795252	19	27	6.31	4.19	0.26						XX		
RR	17	10.5	-705253	32		7.01	4.49	0.31						XX	XX	
FR	18	5.00	-850245	-25.4		2.00	4.00	0.07						XX	XX	
FR	18	8.50	-885250	17.5		5.44	4.06	0.14						XX	XX	
RR	18	10.5	-805253	32		7.01	4.49	0.56						XX	XX	
	601-1412-10	12x1.5 closed lug kit, 10 pk (92 series)												XX		
	601-1412-20	12x1.5 closed lug kit, 20 pk (92 series)												XX		
	601-1422-10	12x1.5 open lug kit, 10 pk (92 series)												XX		
	601-1422-20	12x1.5 open lug kit, 20 pk (92 series)												XX		
	602-2439-10	12x1.5 closed lug kit, 10 pk (95 series)													XX	
	602-2439-20	12x1.5 closed lug kit, 20 pk (95 series)													XX	
CHEVROLET CORVETTE C7 14 up																
14-up Corvette C7 BASE 5x4.75 70.3 56-79 12mm 26"OD																
oe fr	18	8.50		56.00		6.95	2.55			245	40	18	25.72	9.65	3.86	
oe rr	19	10.00		79.00		8.61	2.39			285	35	19	26.85	11.22	3.93	
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		F1	32	82	92	95		
FR	17	4.50	-745245	-12.00		2.28	3.22	0.68						XX	XX	
FR	17	7.00	-770249	22.00		4.87	3.13	0.59						XX	XX	
RR	17	9.50	-795254	52.00		7.30	3.20	0.81						XX		
FR	18	5.00	-850246	-6.00		2.76	3.24	0.69						XX	XX	
FR	18	8.50	-885253	50.00		6.72	2.78	0.24						XX	XX	

RR	18	10.50	-805257	76.00		8.74	2.76	0.37					XX	XX	
	601-1412-10		12x1.5 closed lug kit, 10 pk (92 series)										XX		
	601-1412-20		12x1.5 closed lug kit, 20 pk (92 series)										XX		
	601-1422-10		12x1.5 open lug kit, 10 pk (92 series)										XX		
	601-1422-20		12x1.5 open lug kit, 20 pk (92 series)										XX		
	602-2439-10		12x1.5 closed lug kit, 10 pk (95 series)											XX	
	602-2439-20		12x1.5 closed lug kit, 20 pk (95 series)											XX	
14-up Corvette C7 Z51 5x4.75 70.3 56-79 12mm 26"OD															
FR	19	8.5		56		6.95	2.55			245	35	19	25.75	9.65	3.38
RR	20	10		79		8.61	2.39			285	30	20	26.73	11.22	3.37
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		<i>F1</i>	<i>32</i>	<i>82</i>	<i>92</i>	<i>95</i>	
FR	17	4.50	-745245	-12	-6	2.51	2.99	0.44						XX	
FR	17	7.00	-770249	22	26	5.02	2.98	0.43						XX	
FR	18	5.00	-850246	-6	0	3.00	3.00	0.45						XX	
FR	18	8.50	-885253	50		6.72	2.78	0.24						XX	XX
RR	18	10.5	-805257	76		8.74	2.76	0.37						XX	XX
	601-1412-10		12x1.5 closed lug kit, 10 pk (92 series)											XX	
	601-1412-20		12x1.5 closed lug kit, 20 pk (92 series)											XX	
	601-1422-10		12x1.5 open lug kit, 10 pk (92 series)											XX	
	601-1422-20		12x1.5 open lug kit, 20 pk (92 series)											XX	
	602-2439-10		12x1.5 closed lug kit, 10 pk (95 series)												XX
	602-2439-20		12x1.5 closed lug kit, 20 pk (95 series)												XX
14 up Corvette C7 Z06 5x4.75 70.3 43-59 12mm 26"OD															
FR	19	10		43		7.19	3.81			285	30	19	25.73	11.22	3.37
RR	20	12		59		8.82	4.18			335	25	20	26.59	13.19	3.30
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		<i>F1</i>	<i>32</i>	<i>82</i>	<i>92</i>	<i>95</i>	
FR	17	4.50	-745242	-25.4		1.75	3.75	-0.06						XX	XX
FR	17	7.00	-770247	6.4		4.25	3.75	-0.06						XX	XX
FR	17	9.50	-795252	19	32	6.51	3.99	0.18						XX	
RR	17	9.5	-795252	19		6.00	4.50	0.32						XX	
RR	17	10.5	-705253	32		7.01	4.49	0.31						XX	XX
FR	18	5.00	-850245	-25.4		2.00	4.00	0.19						XX	XX
FR	18	8.50	-885250	17.5		5.44	4.06	0.25						XX	XX
RR	18	10.5	-805253	32		7.01	4.49	0.31						XX	XX

Race Star Wheel Applications

These are recommended fitments for O.E. vehicles.

CADILLAC CTSV COUPE 09 UP/ SEDAN 11 UP

2009-15 CTS-V Coupe 5x120 66.9id 40-55os 14mmx1.5 27.9"OD tire

oe fr	19	9		51		7.007874	2.992126			
oe rr	19	10		40		7.0748031	3.925197			

	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe	92	95
rr	17	9.50	-795252	19.00		6.00	4.50	0.58	XX	
rr	17	10.50	-705253	32.00		7.01	4.49	0.56	XX	XX
fr	18	5.00	-850245	-25.40	-19.4	2.24	3.76	0.77	XX	
fr	18	5.00	-850247	0.00		3.00	3.00	0.01	XX	XX
	18	5.00	-850246	-6.00		2.76	3.24	0.24		XX
fr	18	8.50	-885251	36.00		6.17	3.33	0.34	XX	
rr	18	10.50	-805253	32.00		7.01	4.49	0.56	XX	XX

601-1428-10 14x1.5 closed lug kit, 10 pk (92 series)

601-1428-20 14x1.5 closed lug kit, 20 pk (92 series)

601-1430-10 14x1.5 open lug kit, 10 pk (92 series)

601-1430-20 14x1.5 open lug kit, 20 pk (92 series)

602-2428-10 14x1.5 closed lug kit, 10 pk (95 series)

602-2428-20 14x1.5 closed lug kit, 20 pk (95 series)

2011-13 CTS-V Sedan 5x120 66.9id 40-55os 14mmx1.5 27.3"OD tire

oe fr	19	9.00		51.00		7.01	2.99			
oe rr	19	9.50		56.00		7.45	3.05			

	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe	92	95
fr	18	5.00	-850247	0.00		3.00	3.00	0.01	XX	XX
fr	18	5.00	-850246	-6.00		2.76	3.24	0.24		XX
fr	18	8.50	-885251	36.00		6.17	3.33	0.34	XX	

rr	18	10.50	-805256	57.00		7.99	3.51	0.46		XX	
	601-1428-10		14x1.5 closed lug kit, 10 pk (92 series)							XX	
	601-1428-20		14x1.5 closed lug kit, 20 pk (92 series)							XX	
	601-1430-10		14x1.5 open lug kit, 10 pk (92 series)							XX	
	601-1430-20		14x1.5 open lug kit, 20 pk (92 series)							XX	
	602-2428-10		14x1.5 closed lug kit, 10 pk (95 series)								XX
	602-2428-20		14x1.5 closed lug kit, 20 pk (95 series)								XX

Race Star Wheel Applications

These are recommended fitments for O.E. vehicles.

CHRYSLER/ DODGE/ PLYMOUTH CARS

1970-74 Challenger 5x4.50bc 0-15mm offset 63.91mm 1/2-20

oe fr	14	7.00		0.00	4.00	4.00							
oe rr	14	7.00		0.00	4.00	4.00							
	dia.	width	part # suffix	offset mm	bspace in	fspace in	stick out/ oe		32	82	92	95	
fr	15	3.75	-537140	-25.40	1.38	3.38	-0.63			XX	XX		
fr	15	5.00	-550144	-15.80	2.38	3.62	-0.38				XX		
fr/rr	15	7.00	-570146	-12.70	3.50	4.50	0.50				XX		
fr/rr	15	8.00	-580148	0.00	4.50	4.50	0.50			XX	XX		
rr	15	10.00	-510150	0.00	5.50	5.50	1.50				XX		
fr	17	4.50	-745142	-25.40	1.75	3.75	-0.25			XX	XX	XX	
fr/rr	17	7.00	-770147	6.40	4.25	3.75	-0.25				XX	XX	
fr	18	7.00	-870147	0.00	4.00	4.00	0.00		XX				
rr	18	10.00	-810150	0.00	5.50	5.50	1.50		XX				
fr/rr	20	8.50	-085148	0.00	4.75	4.75	0.75		XX				
rr	20	10.00	-010150	0.00	5.50	5.50	1.50		XX				
	601-1416D-10		1/2-20 closed shank lug kit, 10 pk (82, 92 series)								XX	XX	
	601-1416D-20		1/2-20 closed shank lug kit, 20 pk (82, 92 series)								XX	XX	
	601-1426D-10		1/2-20 open shank lug kit, 10 pk (82, 92 series)								XX	XX	
	601-1426D-20		1/2-20 open shank lug kit, 20 pk (82, 92 series)								XX	XX	
	602-2438-10		1/2-20 closed conical lug kit, 10 pk (32,95 series)						XX				XX
	602-2438-20		1/2-20 closed conical lug kit, 20 pk (32, 95 series)						XX				XX

1966-70 Charger 5x4.50bc 0-15mm offset 63.91mm 1/2-20 (B Body)

oe fr	14	7.00		0.00	4.00	4.00						
oe rr	14	7.00		0.00	4.00	4.00						
	dia.	width	part # suffix	offset mm	bspace in	fspace in	stick out/ oe		32	82	92	95
fr	15	3.75	-537140	-25.40	1.38	3.38	-0.63			XX	XX	
fr	15	5.00	-550144	-15.80	2.38	3.62	-0.38				XX	
fr/rr	15	7.00	-570146	-12.70	3.50	4.50	0.50				XX	
fr/rr	15	8.00	-580148	0.00	4.50	4.50	0.50			XX	XX	
rr	15	10.00	-510150	0.00	5.50	5.50	1.50				XX	
fr	17	4.50	-745142	-25.40	1.75	3.75	-0.25			XX	XX	XX
fr/rr	17	7.00	-770147	6.40	4.25	3.75	-0.25				XX	XX
fr	18	7.00	-870147	0.00	4.00	4.00	0.00		XX			
rr	18	10.00	-810150	0.00	5.50	5.50	1.50		XX			
fr/rr	20	8.50	-085148	0.00	4.75	4.75	0.75		XX			

rr	20	10.00	-010150	0.00	5.50	5.50	1.50		XX			
	601-1416D-10									XX	XX	
	601-1416D-20									XX	XX	
	601-1426D-10									XX	XX	
	601-1426D-20									XX	XX	
	602-2438-10								XX			XX
	602-2438-20								XX			XX
1965-70 Coronet, Super Bee, 500 5x4.50bc 0-15mm offset 63.91mm 1/2-20 (B Body)												
oe fr	14	7.00		0.00	4.00	4.00						
oe rr	14	7.00		0.00	4.00	4.00						
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		32	82	92	95
fr	15	3.75	-537140	-25.40	1.38	3.38	-0.63			XX	XX	
fr	15	5.00	-550144	-15.80	2.38	3.62	-0.38				XX	
fr/rr	15	7.00	-570146	-12.70	3.50	4.50	0.50				XX	
fr/rr	15	8.00	-580148	0.00	4.50	4.50	0.50			XX	XX	
rr	15	10.00	-510150	0.00	5.50	5.50	1.50				XX	
fr	17	4.50	-745142	-25.40	1.75	3.75	-0.25			XX	XX	XX
fr/rr	17	7.00	-770147	6.40	4.25	3.75	-0.25				XX	XX
fr	18	7.00	-870147	0.00	4.00	4.00	0.00		XX			
rr	18	10.00	-810150	0.00	5.50	5.50	1.50		XX			
fr/rr	20	8.50	-085148	0.00	4.75	4.75	0.75		XX			
rr	20	10.00	-010150	0.00	5.50	5.50	1.50		XX			
	601-1416D-10									XX	XX	
	601-1416D-20									XX	XX	
	601-1426D-10									XX	XX	
	601-1426D-20									XX	XX	
	602-2438-10								XX			XX
	602-2438-20								XX			XX
1971-74 Coronet, Super Bee, Charger, R/T 5x4.50bc 0-15mm offset 63.91mm 1/2-20 (B Body)												
oe fr	14	6.00		0.00	3.50	3.50						
oe rr	14	6.00		0.00	3.50	3.50						
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		32	82	92	95
fr	15	3.75	-537140	-25.40	1.38	3.38	-0.13			XX	XX	
fr	15	5.00	-550144	-15.80	2.38	3.62	0.12				XX	
fr/rr	15	7.00	-570146	-12.70	3.50	4.50	1.00				XX	
rr	15	8.00	-580148	0.00	4.50	4.50	1.00			XX	XX	
fr	17	4.50	-745142	-25.40	1.75	3.75	0.25			XX	XX	XX

fr/rr	17	7.00	-770147	6.40	4.25	3.75	0.25				XX	XX	
fr/rr	18	7.00	-870147	0.00	4.00	4.00	0.50		XX				
	601-1416D-10										XX	XX	
	601-1416D-20										XX	XX	
	601-1426D-10										XX	XX	
	601-1426D-20										XX	XX	
	602-2438-10										XX		
	602-2438-20										XX		
1973-80 Dart 5x4.50bc 0-15mm offset 63.91mm 1/2-20 (B Body)													
oe fr	14	6.00		0.00	3.50	3.50							
oe rr	14	6.00		0.00	3.50	3.50							
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>			32	82	92	95
fr	15	3.75	-537140	-25.40	1.38	3.38	-0.13				XX	XX	
fr	15	5.00	-550144	-15.80	2.38	3.62	0.12					XX	
fr/rr	15	7.00	-570146	-12.70	3.50	4.50	1.00					XX	
rr	15	8.00	-580148	0.00	4.50	4.50	1.00				XX	XX	
fr	17	4.50	-745142	-25.40	1.75	3.75	0.25				XX	XX	XX
fr/rr	17	7.00	-770147	6.40	4.25	3.75	0.25					XX	XX
fr/rr	18	7.00	-870147	0.00	4.00	4.00	0.50		XX				
	601-1416D-10										XX	XX	
	601-1416D-20										XX	XX	
	601-1426D-10										XX	XX	
	601-1426D-20										XX	XX	
	602-2438-10										XX		
	602-2438-20										XX		
05-10 Chrysler 300C/SRT, 5x115, 71.5mm id, 14mm x 1.5, OE OD 28.6"													
05-08 Dodge Magnum/RT/SRT, 5x115, 71.5mm id, 14mm x 1.5, OE OD 28.6"													
06-10 Dodge Charger/RT/SRT, 5x115, 71.5mm id, 14mm x 1.5, OE OD 28.6"													
oe fr	20	9.00		20.00		5.79	4.21						
oe rr	20	9.00		20.00		5.79	4.21						
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		32	82	92	95
fr	17	4.50	-745442	-25.40		1.75	3.75	-0.46				XX	XX
fr	17	7.00	-770447	6.40		4.25	3.75	-0.46				XX	XX
rr	17	9.50	-795452	22.50		6.14	4.36	0.15				XX	XX

fr	18	5.00	-850445	-20.00		2.21	3.79	-0.43			XX	XX
fr	18	7.00	-870249	22.00		4.87	3.13	-1.08	XX			
rr	18	10.00	-810253	35.00		6.88	4.12	-0.09	XX			
fr	20	8.50	-085251	35.00		6.13	3.37	-0.84	XX			
rr	20	10.00	-000253	35.00		6.88	4.12	-0.09	XX			
	601-1432-10		14x1.5 closed lug kit, 10 pk (92 series)								XX	
	601-1432-20		14x1.5 closed lug kit, 20 pk (92 series)								XX	
	601-1434-10		14x1.5 open lug kit, 10 pk (92 series)								XX	
	601-1434-20		14x1.5 open lug kit, 20 pk (92 series)								XX	
	602-2428-10		14x1.5 closed lug kit, 10 pk (95 series)						XX			XX
	602-2428-20		14x1.5 closed lug kit, 20 pk (95 series)						XX			XX
12-14 Chrysler 300C/SRT, 5x115, 71.5mm id, 14mm x 1.5, OE OD 28.6"												
12-current Dodge Charger/RT/SRT, 5x115, 71.5mm id, 14mm x 1.5, OE OD 28.6"												
09-current Dodge Challenger/RT/SRT, 5x115, 71.5mm id, 14mm x 1.5, OE OD 28.6"												
oe fr	20	9.00		20.00		5.79	4.21					
oe rr	20	9.00		20.00		5.79	4.21					
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>	32	82	92	95
fr	17	4.50	-745442	-25.40		1.75	3.75	-0.46			XX	XX
fr	17	7.00	-770447	6.40		4.25	3.75	-0.46			XX	XX
rr	17	9.50	-795452	22.50		6.14	4.36	0.15			XX	XX
rr	17	10.50	-705453	27.00		6.81	4.69	0.47			XX	XX
fr	18	5.00	-850445	-20.00		2.21	3.79	-0.43			XX	XX
fr	18	7.00	-870249	22.00		4.87	3.13	-1.08	XX			
rr	18	10.00	-810253	35.00		6.88	4.12	-0.09	XX			
rr	18	10.50	-805453	27.00		6.81	4.69	0.47			XX	XX
fr	20	8.50	-085251	35.00		6.13	3.37	-0.84	XX			
rr	20	10.00	-000253	35.00		6.88	4.12	-0.09	XX			
	601-1432-10		14x1.5 closed lug kit, 10 pk (92 series)								XX	
	601-1432-20		14x1.5 closed lug kit, 20 pk (92 series)								XX	
	601-1434-10		14x1.5 open lug kit, 10 pk (92 series)								XX	

	601-1434-20		14x1.5 open lug kit, 20 pk (92 series)						XX	
	602-2428-10		14x1.5 closed lug kit, 10 pk (95 series)				XX			XX
	602-2428-20		14x1.5 closed lug kit, 20 pk (95 series)				XX			XX

Race Star Wheel Applications

These are recommended fitments for O.E. vehicles.

FORD CARS ALL YEARS

1960-70 Falcon 5x4.50bc 0-15mm offset 63.91mm 1/2-20

oe fr	14	6.00		0.0	3.50	3.50									
oe rr	14	6.00		0.0	3.50	3.50									
	dia.	width	part # suffix	offset mm	bspace in	fspace in	stick out/ oe		F1	32	82	91	92	95	
fr	15	3.75	-537140	-25.4	1.38	3.38	-0.13				XX		XX		
fr	15	5.00	-550144	-15.8	2.38	3.62	0.12						XX		
fr/rr	15	7.00	-570146	-12.7	3.50	4.50	1.00						XX		
fr	17	4.50	-745142	-25.4	1.75	3.75	0.25				XX		XX	XX	
fr/rr	17	7.00	-770147	6.4	4.25	3.75	0.25						XX	XX	
fr/rr	18	7.00	-870147	0.0	4.00	4.00	0.50			XX					
	601-1416D-1	1/2-20 closed shank lug kit, 10 pk (82, 92 series)										XX		XX	
	601-1416D-2	1/2-20 closed shank lug kit, 20 pk (82, 92 series)										XX		XX	
	601-1426D-1	1/2-20 open shank lug kit, 10 pk (82, 92 series)										XX		XX	
	601-1426D-2	1/2-20 open shank lug kit, 20 pk (82, 92 series)										XX		XX	
	602-2438-10	1/2-20 closed conical lug kit, 10 pk (32 series)									XX				
	602-2438-20	1/2-20 closed conical lug kit, 20 pk (32 series)									XX				

1966-67 Fairlane, Torino, Ranchero 5x4.50bc 0-15mm offset 63.91mm 1/2-20

oe fr	14	6.00		0.0	3.50	3.50									
oe rr	14	6.00		0.0	3.50	3.50									
	dia.	width	part # suffix	offset mm	bspace in	fspace in	stick out/ oe		F1	32	82	91	92	95	
fr	15	3.75	-537140	-25.4	1.38	3.38	-0.13				XX		XX		
fr	15	5.00	-550144	-15.8	2.38	3.62	0.12						XX		
fr/rr	15	7.00	-570146	-12.7	3.50	4.50	1.00						XX		
rr	15	8.00	-580148	0.0	4.50	4.50	1.00				XX		XX		
fr	17	4.50	-745142	-25.4	1.75	3.75	0.25				XX		XX	XX	
fr/rr	17	7.00	-770147	6.4	4.25	3.75	0.25						XX	XX	
fr/rr	18	7.00	-870147	0.0	4.00	4.00	0.50			XX					
	601-1416D-1	1/2-20 closed shank lug kit, 10 pk (82, 92 series)										XX		XX	

	601-1416D-2	1/2-20 closed shank lug kit, 20 pk (82, 92 series)								XX		XX		
	601-1426D-1	1/2-20 open shank lug kit, 10 pk (82, 92 series)								XX		XX		
	601-1426D-2	1/2-20 open shank lug kit, 20 pk (82, 92 series)								XX		XX		
	602-2438-10	1/2-20 closed conical lug kit, 10 pk (32 series)								XX				
	602-2438-20	1/2-20 closed conical lug kit, 20 pk (32 series)								XX				
1968-71 Fairlane, Torino, Torino GT, Torino Cobra, Ranchero 5x4.50bc 0-15mm offset 63.91mm 1/2-20														
oe fr	14	6.00		0.0	3.50	3.50								
oe rr	14	6.00		0.0	3.50	3.50								
	dia.	width	part # suffix	offset mm	bspace in	fspace in	stick out/ oe		F1	32	82	91	92	95
fr	15	3.75	-537140	-25.4	1.38	3.38	-0.13				XX		XX	
fr	15	5.00	-550144	-15.8	2.38	3.62	0.12						XX	
fr/rr	15	7.00	-570146	-12.7	3.50	4.50	1.00						XX	
rr	15	8.00	-580148	0.0	4.50	4.50	1.00				XX		XX	
fr	17	4.50	-745142	-25.4	1.75	3.75	0.25				XX		XX	XX
fr/rr	17	7.00	-770147	6.4	4.25	3.75	0.25						XX	XX
fr/rr	18	7.00	-870147	0.0	4.00	4.00	0.50			XX				
	601-1416D-1	1/2-20 closed shank lug kit, 10 pk (82, 92 series)									XX		XX	
	601-1416D-2	1/2-20 closed shank lug kit, 20 pk (82, 92 series)									XX		XX	
	601-1426D-1	1/2-20 open shank lug kit, 10 pk (82, 92 series)									XX		XX	
	601-1426D-2	1/2-20 open shank lug kit, 20 pk (82, 92 series)									XX		XX	
	602-2438-10	1/2-20 closed conical lug kit, 10 pk (32 series)								XX				
	602-2438-20	1/2-20 closed conical lug kit, 20 pk (32 series)								XX				
1972-76 Torino, Gran Torino 5x4.50bc 0-15mm offset 63.91mm 1/2-20														
oe fr	14	6.00		0.0	3.50	3.50								
oe rr	14	6.00		0.0	3.50	3.50								
	dia.	width	part # suffix	offset mm	bspace in	fspace in	stick out/ oe		F1	32	82	91	92	95
fr	15	3.75	-537140	-25.4	1.38	3.38	-0.13				XX		XX	
fr	15	5.00	-550144	-15.8	2.38	3.62	0.12						XX	
fr/rr	15	7.00	-570146	-12.7	3.50	4.50	1.00						XX	
rr	15	8.00	-580148	0.0	4.50	4.50	1.00				XX		XX	

fr	17	4.50	-745142	-25.4	1.75	3.75	0.25				XX		XX	XX
fr/rr	17	7.00	-770147	6.4	4.25	3.75	0.25						XX	XX
fr/rr	18	7.00	-870147	0.0	4.00	4.00	0.50			XX				
		601-1416D-1	1/2-20 closed shank lug kit, 10 pk (82, 92 series)											
		601-1416D-2	1/2-20 closed shank lug kit, 20 pk (82, 92 series)											
		601-1426D-1	1/2-20 open shank lug kit, 10 pk (82, 92 series)											
		601-1426D-2	1/2-20 open shank lug kit, 20 pk (82, 92 series)											
		602-2438-10	1/2-20 closed conical lug kit, 10 pk (32 series)											
		602-2438-20	1/2-20 closed conical lug kit, 20 pk (32 series)											
1971-80 Maverick/ Comet 5x4.50bc 0-15mm offset 63.91mm 1/2-20														
oe fr	14	6.00		0.0	3.50	3.50								
oe rr	14	6.00		0.0	3.50	3.50								
		<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>	<i>F1</i>	<i>32</i>	<i>82</i>	<i>91</i>	<i>92</i>	<i>95</i>
fr	15	3.75	-537140	-25.4	1.38	3.38	-0.13				XX		XX	
fr	15	5.00	-550144	-15.8	2.38	3.62	0.12						XX	
fr/rr	15	7.00	-570146	-12.7	3.50	4.50	1.00						XX	
rr	15	8.00	-580148	0.0	4.50	4.50	1.00				XX		XX	
fr	17	4.50	-745142	-25.4	1.75	3.75	0.25				XX		XX	XX
fr/rr	17	7.00	-770147	6.4	4.25	3.75	0.25						XX	XX
fr/rr	18	7.00	-870147	0.0	4.00	4.00	0.50			XX				
		601-1416D-1	1/2-20 closed shank lug kit, 10 pk (82, 92 series)											
		601-1416D-2	1/2-20 closed shank lug kit, 20 pk (82, 92 series)											
		601-1426D-1	1/2-20 open shank lug kit, 10 pk (82, 92 series)											
		601-1426D-2	1/2-20 open shank lug kit, 20 pk (82, 92 series)											
		602-2438-10	1/2-20 closed conical lug kit, 10 pk (32 series)											
		602-2438-20	1/2-20 closed conical lug kit, 20 pk (32 series)											

rr	18	10.00	-810551	12.70		6.00	5.00	1.00		XX		
fr	20	8.50	-085549	6.40		5.00	4.50	0.50		XX		
rr	20	10.00	-010551	12.00		5.97	5.03	1.03		XX		
		601-1410-10	14x2 closed lug kit, 10 pk (92 series)								XX	
		601-1410-20	14x2 closed lug kit, 20 pk (92 series)								XX	
		602-2410-10	14x2 closed lug kit, 10 pk (32 series)							XX		
		602-2410-20	14x2 closed lug kit, 20 pk (32 series)							XX		
04-14 F150 2wd 6x135 87.0 30-40 14x2.00												
oe fr/rr	17	7.50		44.00		5.98	2.52					
oe rr/rr	18	7.50		44.00		5.98	2.52					
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		32	92	93
fr	17	4.50	-745742	-25.40		1.75	3.75	1.23				XX
fr	17	7.00	-770747	6.40		4.25	3.75	1.23				XX
rr	17	9.50	-795752	25.00		6.23	4.27	1.75				XX
fr	18	7.00	-870747	6.00		4.24	3.76	1.25		XX		
rr	18	10.00	-810752	32.00		6.76	4.24	1.72		XX		
fr	20	8.50	-085750	25.00		5.73	3.77	1.25		XX		
rr	20	10.00	-010752	32.00		6.76	4.24	1.72		XX		
		602-2410-12	14x2 closed lug kit, 12 pk							XX		XX
		602-2410-24	14x2 closed lug kit, 24 pk							XX		XX
93-96 F150 LIGHTNING 2wd 5x5.5 87.0 0-15 1/2-20												
oe fr/rr	17	8.00		0.00		4.50	4.50					
oe rr/rr	17	8.00		0.00		4.50	4.50					
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		32	92	93
rr	15	10.00	-510540	-4.80		5.31	5.69	1.19			XX	
fr	17	4.50	-745532	-25.40		1.75	3.75	-0.75			XX	
fr	17	7.00	-770847	6.40		4.25	3.75	-0.75			XX	
rr	17	10.50	-705851	9.00		6.10	5.40	0.90			XX	
fr	18	7.00	-870847	0.00		4.00	4.00	-0.50		XX		
rr	18	10.00	-810851	12.70		6.00	5.00	0.50		XX		
fr	20	8.50	-085849	6.40		5.00	4.50	0.00		XX		
rr	20	10.00	-010851	12.00		5.97	5.03	0.53		XX		

rr	15	10.00	-510150	0.00	5.50	5.50	1.97					XX
fr	17	4.50	-745142	-25.40	1.75	3.75	0.72					XX
fr/rr	17	7.00	-770147	6.40	4.25	3.75	0.72					XX
fr	18	7.00	-870147	0.00	4.00	4.00	0.97				XX	
rr	18	10.00	-810150	0.00	5.50	5.50	1.97				XX	
fr/rr	20	8.50	-085148	0.00	4.75	4.75	1.72				XX	
rr	20	10.00	-010150	0.00	5.50	5.50	1.97				XX	
	601-1416D-10		1/2-20 closed shank lug kit, 10 pk (82, 92 series)									XX
	601-1416D-20		1/2-20 closed shank lug kit, 20 pk (82, 92 series)									XX
	601-1426D-10		1/2-20 open shank lug kit, 10 pk (82, 92 series)									XX
	601-1426D-20		1/2-20 open shank lug kit, 20 pk (82, 92 series)									XX
	602-2438-10		1/2-20 closed conical lug kit, 10 pk (32,95 series)									XX
	602-2438-20		1/2-20 closed conical lug kit, 20 pk (32, 95 series)									XX

Race Star Wheel Applications

These are recommended fitments for O.E. vehicles.

MERCURY CARS ALL YEARS

1966-67 Comet, Cyclone 5x4.50bc 0-15mm offset 63.91mm 1/2-20

oe fr	14	6.00		0.0	3.50	3.50									
oe rr	14	6.00		0.0	3.50	3.50									
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>	32	82	91	92	95	<i>notes</i>	<i>c/c</i>	
fr	15	3.75	-537140	-25.4	1.38	3.38	-0.13		XX		XX				
fr	15	5.00	-550144	-15.8	2.38	3.62	0.12				XX				
fr/rr	15	7.00	-570146	-12.7	3.50	4.50	1.00				XX				
rr	15	8.00	-580148	0.0	4.50	4.50	1.00		XX		XX				
fr	17	4.50	-745142	-25.4	1.75	3.75	0.25		XX		XX	XX			
fr/rr	17	7.00	-770147	6.4	4.25	3.75	0.25				XX	XX			
fr/rr	18	7.00	-870147	0.0	4.00	4.00	0.50	XX							
	601-1416D-10	1/2-20 closed shank lug kit, 10 pk (82, 92 series)								XX		XX			
	601-1416D-20	1/2-20 closed shank lug kit, 20 pk (82, 92 series)								XX		XX			
	601-1426D-10	1/2-20 open shank lug kit, 10 pk (82, 92 series)								XX		XX			
	601-1426D-20	1/2-20 open shank lug kit, 20 pk (82, 92 series)								XX		XX			
	602-2438-10	1/2-20 closed conical lug kit, 10 pk (32 series)						XX							
	602-2438-20	1/2-20 closed conical lug kit, 20 pk (32 series)						XX							

1967-68 Cougar 5x4.50bc 0-15mm offset 63.91mm 1/2-20

oe fr	14	6.00		0.0	3.50	3.50									
oe rr	14	6.00		0.0	3.50	3.50									
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>	32	82	91	92	95	<i>notes</i>	<i>c/c</i>	
fr	15	3.75	-537140	-25.4	1.38	3.38	-0.13		XX		XX				
fr	15	5.00	-550144	-15.8	2.38	3.62	0.12				XX				
fr/rr	15	7.00	-570146	-12.7	3.50	4.50	1.00				XX				
rr	15	8.00	-580148	0.0	4.50	4.50	1.00		XX		XX				
fr	17	4.50	-745142	-25.4	1.75	3.75	0.25		XX		XX	XX			
fr/rr	17	7.00	-770147	6.4	4.25	3.75	0.25				XX	XX			
fr/rr	18	7.00	-870147	0.0	4.00	4.00	0.50	XX							
	601-1416D-10	1/2-20 closed shank lug kit, 10 pk (82, 92 series)								XX		XX			
	601-1416D-20	1/2-20 closed shank lug kit, 20 pk (82, 92 series)								XX		XX			
	601-1426D-10	1/2-20 open shank lug kit, 10 pk (82, 92 series)								XX		XX			
	601-1426D-20	1/2-20 open shank lug kit, 20 pk (82, 92 series)								XX		XX			
	602-2438-10	1/2-20 closed conical lug kit, 10 pk (32 series)						XX							
	602-2438-20	1/2-20 closed conical lug kit, 20 pk (32 series)						XX							

1969-73 Cougar 5x4.50bc 0-15mm offset 63.91mm 1/2-20

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

oe fr	14	7.00		0.00	4.00	4.00									
oe rr	14	7.00		0.00	4.00	4.00									
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>	32	82	91	92	95	<i>notes</i>	<i>c/c</i>	
fr	15	3.75	-537140	-25.40	1.38	3.38	-0.63		XX		XX				
fr	15	5.00	-550144	-15.80	2.38	3.62	-0.38				XX				
fr/rr	15	7.00	-570146	-12.70	3.50	4.50	0.50				XX				
fr/rr	15	8.00	-580148	0.00	4.50	4.50	0.50		XX		XX				
rr	15	10.00	-510150	0.00	5.50	5.50	1.50				XX				
fr	17	4.50	-745142	-25.40	1.75	3.75	-0.25		XX		XX	XX			
fr/rr	17	7.00	-770147	6.40	4.25	3.75	-0.25				XX	XX			
fr	18	7.00	-870147	0.00	4.00	4.00	0.00	XX							
rr	18	10.00	-810150	0.00	5.50	5.50	1.50	XX							
fr/rr	20	8.50	-085148	0.00	4.75	4.75	0.75	XX							
rr	20	10.00	-010150	0.00	5.50	5.50	1.50	XX							
	601-1416D-10		1/2-20 closed shank lug kit, 10 pk (82, 92 series)						XX		XX				
	601-1416D-20		1/2-20 closed shank lug kit, 20 pk (82, 92 series)						XX		XX				
	601-1426D-10		1/2-20 open shank lug kit, 10 pk (82, 92 series)						XX		XX				
	601-1426D-20		1/2-20 open shank lug kit, 20 pk (82, 92 series)						XX		XX				
	602-2438-10		1/2-20 closed conical lug kit, 10 pk (32,95 series)					XX				XX			
	602-2438-20		1/2-20 closed conical lug kit, 20 pk (32, 95 series)					XX				XX			

Race Star Wheel Applications

These are recommended fitments for O.E. vehicles.

FORD MUSTANG ALL YEARS

1964-66 Mustang 5x4.50bc 0-15mm offset 63.91mm 1/2-20 (oe = 14x6 @ 3.50 backspace, 25.5" OD)

oe fr	14	6.00		0.0	3.50	3.50								
oe rr	14	6.00		0.0	3.50	3.50								
	dia.	width	part # suffix	offset mm	bspace in	fspace in	stick out/ oe		F1	32	82	91	92	95
fr	15	3.75	-537140	-25.4	1.38	3.38	-0.13				XX		XX	
fr	15	5.00	-550144	-15.8	2.38	3.62	0.12						XX	
fr/rr	15	7.00	-570146	-12.7	3.50	4.50	1.00						XX	
rr	15	8.00	-580148	0.0	4.50	4.50	1.00				XX		XX	
fr	17	4.50	-745142	-25.4	1.75	3.75	0.25				XX		XX	XX
fr/rr	17	7.00	-770147	6.4	4.25	3.75	0.25						XX	XX
fr/rr	18	7.00	-870147	0.0	4.00	4.00	0.50			XX				
			601-1416D-10								XX		XX	
			601-1416D-20								XX		XX	
			601-1426D-10								XX		XX	
			601-1426D-20								XX		XX	
			602-2438-10								XX			
			602-2438-20								XX			

1967-68 Mustang 5x4.50bc 0-15mm offset 63.91mm 1/2-20 (oe = 14x6 @ 3.50 backspace)

oe fr	14	6.00		0.00	3.50	3.50								
oe rr	14	6.00		0.00	3.50	3.50								
	dia.	width	part # suffix	offset mm	bspace in	fspace in	stick out/ oe		F1	32	82	91	92	95
fr	15	3.75	-537140	-25.40	1.38	3.38	-0.13				XX		XX	
fr	15	5.00	-550144	-15.80	2.38	3.62	0.12						XX	
fr/rr	15	7.00	-570146	-12.70	3.50	4.50	1.00						XX	
rr	15	8.00	-580148	0.00	4.50	4.50	1.00				XX		XX	
fr	17	4.50	-745142	-25.40	1.75	3.75	0.25				XX		XX	XX
fr/rr	17	7.00	-770147	6.40	4.25	3.75	0.25						XX	XX
fr/rr	18	7.00	-870147	0.00	4.00	4.00	0.50			XX				
			601-1416D-10								XX		XX	
			601-1416D-20								XX		XX	

	601-1426D-10		1/2-20 open shank lug kit, 10 pk (82, 92 series)									XX		XX	
	601-1426D-20		1/2-20 open shank lug kit, 20 pk (82, 92 series)									XX		XX	
	602-2438-10		1/2-20 closed conical lug kit, 10 pk (32 series)									XX			
	602-2438-20		1/2-20 closed conical lug kit, 20 pk (32 series)									XX			
1969-73 Mustang 5x4.50bc 0-15mm offset 63.91mm 1/2-20 (oe = 14x7 or 15x7 @ 4.00 backspace)															
oe fr	14	7.00		0.00	4.00	4.00									
oe rr	14	7.00		0.00	4.00	4.00									
	dia.	width	part # suffix	offset mm	bspace in	fspace in	stick out/ oe		F1	32	82	91	92	95	
fr	15	3.75	-537140	-25.40	1.38	3.38	-0.63				XX		XX		
fr	15	5.00	-550144	-15.80	2.38	3.62	-0.38						XX		
fr/rr	15	7.00	-570146	-12.70	3.50	4.50	0.50						XX		
fr/rr	15	8.00	-580148	0.00	4.50	4.50	0.50				XX		XX		
rr	15	10.00	-510150	0.00	5.50	5.50	1.50						XX		
fr	17	4.50	-745142	-25.40	1.75	3.75	-0.25				XX		XX	XX	
fr/rr	17	7.00	-770147	6.40	4.25	3.75	-0.25						XX	XX	
fr	18	7.00	-870147	0.00	4.00	4.00	0.00			XX					
rr	18	10.00	-810150	0.00	5.50	5.50	1.50			XX					
fr/rr	20	8.50	-085148	0.00	4.75	4.75	0.75			XX					
rr	20	10.00	-010150	0.00	5.50	5.50	1.50			XX					
	601-1416D-10		1/2-20 closed shank lug kit, 10 pk (82, 92 series)									XX		XX	
	601-1416D-20		1/2-20 closed shank lug kit, 20 pk (82, 92 series)									XX		XX	
	601-1426D-10		1/2-20 open shank lug kit, 10 pk (82, 92 series)									XX		XX	
	601-1426D-20		1/2-20 open shank lug kit, 20 pk (82, 92 series)									XX		XX	
	602-2438-10		1/2-20 closed conical lug kit, 10 pk (32,95 series)									XX			XX
	602-2438-20		1/2-20 closed conical lug kit, 20 pk (32, 95 series)									XX			XX
1974-78 Mustang 4x4.25(108) 15-25mm offset 63.4mm 1/2-20 (oe = 13x7 @4.50 backspace)															
oe fr	13	7.00		0.00	4.00	4.00									
oe rr	13	7.00		0.00	4.00	4.00									
	dia.	width	part # suffix	offset mm	bspace in	fspace in	stick out/ oe		F1	32	82	91	92	95	
fr	15	3.75	-537021	-22.20	1.50	3.25	-0.75						XX		
fr/rr	15	8.00	-580030	25.40	5.50	3.50	-0.50						XX		
	603-1435-8		1/2-20 closed lug kit, 8 pk (91 series)											XX	

	603-1435-16	1/2-20 closed lug kit, 16 pk (91 series)										XX		
1979-93 Mustang 4x4.25(108) 15-25mm offset 63.4mm 1/2-20 (oe = 14x7 @4.50 backspace)														
oe fr	14	7.00		0.00	4.00	4.00								
oe rr	14	7.00		0.00	4.00	4.00								
	dia.	width	part # suffix	offset mm	bspace in	fspace in	stick out/ oe	F1	32	82	91	92	95	
fr	15	3.75	-537021	-22.20	1.50	3.25	-0.75				XX			
fr/rr	15	8.00	-580030	25.40	5.50	3.50	-0.50				XX			
rr	15	10.00	-510032	25.40	6.50	4.50	0.50				XX			
	603-1435-8	1/2-20 closed lug kit, 8 pk (91 series)										XX		
	603-1435-16	1/2-20 closed lug kit, 16 pk (91 series)										XX		
1979-93 Mustang 5x4.50 lug conversion 15-25mm offset 63.4mm 1/2-20 (oe = 14x7 @4.50 backspace)														
oe fr	14	7.00		15.00	4.59	3.41								
oe rr	14	7.00		15.00	4.59	3.41								
	dia.	width	part # suffix	offset mm	bspace in	fspace in	stick out/ oe	F1	32	82	91	92	95	
fr	15	3.75	-537140	-25.40	1.38	3.38	-0.03			XX		XX		
fr	15	5.00	-550144	-15.80	2.38	3.62	0.21					XX		
fr/rr	15	7.00	-570146	-12.70	3.50	4.50	1.09					XX		
fr/rr	15	8.00	-580150	19.00	5.25	3.75	0.34			XX		XX		
rr	15	10.00	-510152	19.00	6.25	4.75	1.34			XX		XX		
fr	17	4.50	-745142	-25.40	1.75	3.75	0.34			XX		XX	XX	
fr/rr	17	7.00	-770147	6.40	4.25	3.75	0.34					XX	XX	
rr	17	9.50	-795152	22.50	6.14	4.36	0.95					XX		
fr	18	7.00	-870148	12.70	4.50	3.50	0.09		XX					
rr	18	10.00	-810152	25.00	6.48	4.52	1.11		XX					
rr	20	10.00	-010152	25.00	6.48	4.52	1.11		XX					
	601-1416D-10	1/2-20 closed shank lug kit, 10 pk (82, 92 series)									XX		XX	
	601-1416D-20	1/2-20 closed shank lug kit, 20 pk (82, 92 series)									XX		XX	
	601-1426D-10	1/2-20 open shank lug kit, 10 pk (82, 92 series)									XX		XX	
	601-1426D-20	1/2-20 open shank lug kit, 20 pk (82, 92 series)									XX		XX	
	602-2438-10	1/2-20 closed conical lug kit, 10 pk (32,95 series)								XX				XX
	602-2438-20	1/2-20 closed conical lug kit, 20 pk (32, 95 series)								XX				XX
1994-2004 Mustang 5x4.50bc 15-25mm offset 70.5mm 1/2-20														
oe fr	17	8.00		15.00	5.09	3.91								

oe rr	17	8.00		15.00	5.09	3.91								
	dia.	width	part # suffix	offset mm	bsp space in	fspace in	stick out/ oe		F1	32	82	91	92	95
fr	15	3.75	-537140	-25.40	1.38	3.38	-0.53				XX		XX	
fr	15	5.00	-550144	-15.80	2.38	3.62	-0.29						XX	
fr	15	7.00	-570146	-12.70	3.50	4.50	0.59						XX	
fr/rr	15	8.00	-580150	19.00	5.25	3.75	-0.16				XX		XX	
rr	15	10.00	-510152	19.00	6.25	4.75	0.84							
fr	17	4.50	-745142	-25.40	1.75	3.75	-0.16				XX		XX	XX
fr/rr	17	7.00	-770147	6.40	4.25	3.75	-0.16						XX	XX
rr	17	9.50	-795152	22.50	6.14	4.36	0.45						XX	
fr	18	7.00	-870148	12.70	4.50	3.50	-0.41			XX				
rr	18	10.00	-810152	25.00	6.48	4.52	0.61			XX				
rr	20	10.00	-010152	25.00	6.48	4.52	0.61			XX				
	601-1416D-10	1/2-20 closed shank lug kit, 10 pk (82, 92 series)									XX		XX	
	601-1416D-20	1/2-20 closed shank lug kit, 20 pk (82, 92 series)									XX		XX	
	601-1426D-10	1/2-20 open shank lug kit, 10 pk (82, 92 series)									XX		XX	
	601-1426D-20	1/2-20 open shank lug kit, 20 pk (82, 92 series)									XX		XX	
	602-2438-10	1/2-20 closed conical lug kit, 10 pk (32,95 series)									XX			XX
	602-2438-20	1/2-20 closed conical lug kit, 20 pk (32, 95 series)									XX			XX
2005-2014 Mustang 5x4.50bc 35-45mm offset 70.5mm 1/2-20														
oe fr	17	8.00		45.00	6.27	2.73								
	19	9.00		42.00	6.65	3.35								
oe rr	18	9.50		45.00	7.02	3.48								
	19	10.00		47.50	7.37	3.63								
	dia.	width	part # suffix	offset mm	bsp space in	fspace in	stick out/ oe		F1	32	82	91	92	95
fr	15	3.75	-537140	-25.40	1.38	3.38	0.65						XX	
fr	15	5.00	-550144	-15.80	2.38	3.62	0.89						XX	
rr	15	8.00	-580150	19.00	5.25	3.75	3.75				XX		XX	
rr	15	10.00	-510154	44.00	7.23	3.77	3.77		XX		XX		XX	XX
fr	17	4.50	-745142	-25.40	1.75	3.75	0.27		XX		XX		XX	XX
fr	17	7.00	-770147	6.40	4.25	3.75	0.27						XX	XX
rr	17	9.50	-795153	43.50	6.96	3.54	#VALUE!						XX	
rr	17	10.50	-705154	48.00	7.64	3.86	#VALUE!						XX	XX
fr	18	5.00	-850145	-25.40	2.00	4.00	0.63						XX	XX
fr	18	7.00	-870149	25.00	4.98	3.02	3.02			XX				
fr/rr	18	8.50	-885152	28.00	5.85	3.65	0.03						XX	XX

rr	18	10.00	-800153	35.00	6.88	4.12	0.78			XX				
rr	18	10.50	-805154	48.00	7.64	3.86	0.23						XX	XX
fr/rr	20	9.00	-090152	34.00	6.34	3.66	-0.11						XX	
fr/rr	20	8.50	-085151	35.00	6.13	3.37	0.64			XX				
rr	20	10.00	-000153	35.00	6.88	4.12	0.64			XX				
	601-1416D-10		1/2-20 closed shank lug kit, 10 pk (82, 92 series)								XX		XX	
	601-1416D-20		1/2-20 closed shank lug kit, 20 pk (82, 92 series)								XX		XX	
	601-1426D-10		1/2-20 open shank lug kit, 10 pk (82, 92 series)								XX		XX	
	601-1426D-20		1/2-20 open shank lug kit, 20 pk (82, 92 series)								XX		XX	
	602-2438-10		1/2-20 closed conical lug kit, 10 pk (32,95 series)						XX	XX				XX
	602-2438-20		1/2-20 closed conical lug kit, 20 pk (32, 95 series)						XX	XX				XX
2015-UP Mustang (NON Track Pack) x4.50bc 35-45mm offset 70.5mm 14mm, INDEPENDENT REAR														
oe fr	19	9.00		45.00	6.77	3.23								
oe rr	19	9.50		52.50	7.32	3.18								
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		<i>F1</i>	<i>32</i>	<i>82</i>	<i>91</i>	<i>92</i>	<i>95</i>
rr	15	8.00	-580150	19.00	5.25	3.75	3.75						XX	
fr	17	4.50	-745142	-25.40	1.75	3.75	0.57		XX				XX	XX
fr	17	7.00	-770147	18.00	4.71	3.29	0.11						XX	XX
rr	17	9.50	-795153	43.50	6.96	3.54	3.54						XX	
rr	17	10.50	-705154	48.00	7.64	3.86	3.86						XX	XX
fr	18	5.00	-850145	-25.40	2.00	4.00	0.25						XX	XX
fr	18	8.50	-885152	28.00	5.85	3.65	-0.10						XX	XX
rr	18	10.50	-805154	48.00	7.64	3.86	0.63						XX	XX
fr	20	9.00	-090152	34.00	6.34	3.66	0.37						XX	
rr	20	9.00	-090152	34.00	6.34	3.66	0.48						XX	
	601-1429-10		14x1.5 closed lug kit, 10 pk (92 series)										XX	
	601-1429-20		14x1.5 closed lug kit, 20 pk (92 series)										XX	
	601-1433-10		14x1.5 open lug kit, 10 pk (92 series)										XX	
	601-1433-20		14x1.5 open lug kit, 20 pk (92 series)										XX	
	602-2428-10		14x1.5 closed lug kit, 10 pk (95 series)											XX
	602-2428-20		14x1.5 closed lug kit, 20 pk (95 series)											XX
2015-UP Mustang (Track Pack) x4.50bc 35-45mm offset 70.5mm 14mm, INDEPENDENT REAR														

Race Star Wheel Applications

These are recommended fitments for O.E. vehicles.

PONTIAC ALL YEARS

2004-06 Pontiac GTO 5x120 69.5id 35-45os 12mmx1.5 25.7"OD tire

oe fr	17	8.00		45.00		6.27	2.73							
	18	8.00		45.00		6.27	2.73							
oe rr	17	8.00		45.00		6.27	2.73							
	18	8.00		45.00		6.27	2.73							

	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		F1	32	82	92	95
fr	15	3.75	-537240	-28.70		1.25	3.50	0.78				XX	XX	
rr	15	8.00	-580250	19.00		5.25	3.75	1.02				XX	XX	
rr	15	10.00	-510254	44.00		7.23	3.77	1.04		XX		XX	XX	XX
fr	17	4.50	-745242	-25.40	-12.00	2.28	3.22	0.49				XX	XX	
fr	17	4.50	-745245	-12.00		2.28	3.22	0.49		XX			XX	XX
fr	17	7.00	-770249	22.00		4.87	3.13	0.41					XX	XX
fr/rr	17	8.00	-780250	25.40		5.50	3.50	0.77					XX	
rr	17	9.50	-795253	43.50		6.96	3.54	0.81					XX	
fr	18	5.00	-850246	-6.00		2.76	3.24	0.51					XX	XX
fr	18	7.00	-870249	20.00		4.79	3.21	0.48			XX			
fr/rr	18	8.50	-885251	36.00		6.17	3.33	0.60					XX	
rr	18	10.00	-810253	44.00		7.23	3.77	1.04			XX			
fr/rr	20	8.50	-085251	35.00		6.13	3.37	0.64			XX			
rr	20	10.00	-000253	44.00		7.23	3.77	1.04			XX			
			601-1412-10										XX	XX
			601-1412-20										XX	XX
			601-1422-10										XX	XX
			601-1422-20										XX	XX
			602-2439-10							XX	XX			XX
			602-2439-20							XX	XX			XX

2008-09 G8 5x120 66.9id 35-45os 14mmx1.5 26.7"OD tire

oe fr	18.00	8.00		48.00		6.39	2.61							
	19.00	8.00		48.00		6.39	2.61							
oe rr	18.00	8.00		48.00		6.39	2.61							
	19.00	8.00		48.00		6.39	2.61							

	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		<i>F1</i>	<i>32</i>	<i>82</i>	<i>92</i>	<i>95</i>
fr	17	4.50	-745242	-25.40		1.75	3.75	1.14		XX			XX	XX
fr	17	7.00	-770247	6.40		4.25	3.75	1.14					XX	XX
fr/rr	17	8.00	-780250	25.40		5.50	3.50	0.89					XX	
rr	17	9.50	-795253	43.50		6.96	3.54	0.93					XX	
rr	17	10.50	-705253	32.00	51.00	7.76	3.74	1.13					XX	
fr	18	5.00	-850246	-6.00		2.76	3.24	0.63					XX	XX
fr/rr	18	8.50	-885251	36.00		6.17	3.33	0.72					XX	
rr	18	10.50	-805253	32.00	51.00	7.76	3.74	1.13					XX	
	601-1428-10		14x1.5 closed lug kit, 10 pk (92 series)										XX	XX
	601-1428-20		14x1.5 closed lug kit, 20 pk (92 series)										XX	XX
	601-1430-10		14x1.5 open lug kit, 10 pk (92 series)										XX	XX
	601-1430-20		14x1.5 open lug kit, 20 pk (92 series)										XX	XX
	602-2428-10		14x1.5 closed lug kit, 10 pk (95 series)							XX	XX			XX
	602-2428-20		14x1.5 closed lug kit, 20 pk (95 series)							XX	XX			XX

Race Star Wheel Applications

These are recommended fitments for O.E. vehicles.

DODGE/ RAM 1500 TRUCK ALL YEARS

94-01 RAM 1500 5x5.50 77.8 1/2-20

									W/ mm	RATIO	DIA	OD	S/W	SW/H	
oe fr/rr	16	7.00		25.00		4.98	3.02		225	75	16	29.29	8.86	6.64	
oe rr/rr	16	7.00		25.00		4.98	3.02		245	75	16	30.47	9.65	7.23	
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		32	92				
fr	17	7.00	-770847	6.40		4.25	3.75	0.73			XX				
rr	17	10.50	-705852	20.00		6.54	4.96	1.95			XX				
rr	20	8.50	-085848	0.00		4.75	4.75	1.73		XX					
	20	10.00	-010852	13.00		6.01	4.99	1.97		XX					
	601-1416D-10	1/2-20 closed shank lug kit, 10 pk (92 series)											XX		
	601-1416D-20	1/2-20 closed shank lug kit, 20 pk (92 series)											XX		
	601-1426D-10	1/2-20 open shank lug kit, 10 pk (92 series)											XX		
	601-1426D-20	1/2-20 open shank lug kit, 20 pk (92 series)											XX		
	602-2438-10	1/2-20 closed conical lug kit, 10 pk (32 series)											XX		
	602-2438-20	1/2-20 closed conical lug kit, 20 pk (32 series)											XX		

02-11 RAM 1500 5x5.50 77.8 9/16

									W/ mm	RATIO	DIA	OD	S/W	SW/H	
oe fr/rr	16	7.00		25.00		4.98	3.02		225	75	16	29.29	8.86	6.64	
oe rr/rr	16	7.00		25.00		4.98	3.02		245	75	16	30.47	9.65	7.23	
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		32	92				
fr	17	7.00	-770847	6.40		4.25	3.75	0.73			XX				
rr	17	10.50	-705852	20.00		6.54	4.96	1.95			XX				
rr	20	8.50	-085848	0.00		4.75	4.75	1.73		XX					
	20	10.00	-010852	13.00		6.01	4.99	1.97		XX					
	601-1411-10	9/16 closed shank lug kit, 10 pk (92 series)											XX		
	601-1411-20	9/16 closed shank lug kit, 20 pk (92 series)											XX		

12-13 RAM 1500 5x5.50 77.8 9/16 or 14x1.5

									W/ mm	RATIO	DIA	OD	S/W	SW/H
oe fr/rr	17	8.00		25.40		5.50	3.50		265	70	17	31.61	10.43	7.30
oe rr/rr	20	9.00		19.00		5.75	4.25		275	60	20	32.99	10.83	6.50
	dia.	width	part # suffix	offset mm	adj offset	bspace in	fspace in	stick out/ oe		32	92			
fr	17	7.00	-770847	6.40		4.25	3.75	0.25			XX			
rr	17	10.50	-705852	20.00		6.54	4.96	0.71			XX			
rr	20	8.50	-085848	0.00		4.75	4.75	0.50		XX				

	20	10.00	-010852	13.00		6.01	4.99	0.74		XX				
	601-1411-10		9/16 closed shank lug kit, 10 pk (92 series)								XX			
	601-1411-20		9/16 closed shank lug kit, 20 pk (92 series)								XX			
	601-1428-10		14x1.5 closed lug kit, 10 pk (92 series)								XX			
	601-1428-20		14x1.5 closed lug kit, 20 pk (92 series)								XX			
	602-2428-10		14x1.5 closed lug kit, 10 pk (32 series)							XX				
	602-2428-20		14x1.5 closed lug kit, 20 pk (32 series)							XX				
14-up RAM 1500 5x5.50 77.8 14x1.5														
oe fr/rr	17	7.00		25.40		5.00	3.00		W/ mm	RATIO	DIA	OD	S/W	SW/H
oe rr/rr	20	9.00		19.00		5.75	4.25		265	70	17	31.61	10.43	7.30
									275	60	20	32.99	10.83	6.50
	<i>dia.</i>	<i>width</i>	<i>part # suffix</i>	<i>offset mm</i>	<i>adj offset</i>	<i>bspace in</i>	<i>fspace in</i>	<i>stick out/ oe</i>		32	92			
fr	17	7.00	-770847	6.40		4.25	3.75	0.75			XX			
rr	17	10.50	-705852	20.00		6.54	4.96	0.71			XX			
rr	20	8.50	-085848	0.00		4.75	4.75	0.50		XX				
	20	10.00	-010852	13.00		6.01	4.99	0.74		XX				
	601-1428-10		14x1.5 closed lug kit, 10 pk (92 series)								XX			
	601-1428-20		14x1.5 closed lug kit, 20 pk (92 series)								XX			
	602-2428-10		14x1.5 closed lug kit, 10 pk (32 series)							XX				
	602-2428-20		14x1.5 closed lug kit, 20 pk (32 series)							XX				